



(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 125 284 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:

06.08.2003 Bulletin 2003/32

(51) Int Cl.7: G10L 21/02

(21) Application number: 99952183.4

(86) International application number:
PCT/CA99/00990

(22) Date of filing: 27.10.1999

(87) International publication number:
WO 00/025305 (04.05.2000 Gazette 2000/18)

(54) HIGH FREQUENCY CONTENT RECOVERING METHOD AND DEVICE FOR OVER-SAMPLED SYNTHESIZED WIDEBAND SIGNAL

VORRICHTUNG UND VERFAHREN ZUR WIEDERHERSTELLUNG DES
HOCHFREQUENZANTEILS EINES ÜBERABGETASTETEN SYNTHEZISIERTEN
BREITBANDSIGNALS

PROCEDE DE RECUPERATION DU CONTENU A HAUTE FREQUENCE ET DISPOSITIF POUR
SIGNAL A LARGE BANDE SYNTHEZISE SUR-ECHANTILLONNE

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE

(74) Representative: W.P. THOMPSON & CO.

Eastcheap House
Central Approach
Letchworth Garden City,
Hertfordshire SG6 3DS (GB)

(30) Priority: 27.10.1998 CA 2252170

(56) References cited:

EP-A- 0 838 804 US-A- 5 455 888

(43) Date of publication of application:

22.08.2001 Bulletin 2001/34

- CARM H ET AL: "BANDWIDTH ENHANCEMENT OF NARROW-BAND SPEECH SIGNALS" SIGNAL PROCESSING: THEORIES AND APPLICATIONS, XX, XX, page 1178-1181 XP000783776
- YAN MING CHENG ET AL: "Statistical recovery of wideband speech from narrowband speech" IEEE TRANSACTIONS ON SPEECH AND AUDIO PROCESSING, OCT. 1994, USA, vol. 2, no. 4, pages 544-548, XP000874178 ISSN: 1063-6676

(73) Proprietor: Voiceage Corporation

Ville Mont-Royal, Quebec H3R 2H6 (CA)

(72) Inventors:

- BESSETTE, Bruno
Rock Forest, Quebec J1N 1L2 (CA)
- SALAMI, Redwan
Sherbrooke, Quebec J1J 4L3 (CA)
- LEFEBVRE, Roch
Canton de Magog, Quebec J1K 5R9 (CA)

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

5 1. Field of the invention:

[0001] The present invention relates to a method and device for recovering a high frequency content of a wideband signal previously down-sampled, and for injecting this high frequency content in an over-sampled synthesized version of the down-sampled wideband signal to produce a full-spectrum synthesized wideband signal.

10 2. Brief description of the prior art:

[0002] The demand for efficient digital wideband speech/audio encoding techniques with a good subjective quality/bit rate trade-off is increasing for numerous applications such as audio/video teleconferencing, multimedia, and wireless applications, as well as Internet and packet network applications. Until recently, telephone bandwidths filtered in the range 200-3400 Hz were mainly used in speech coding applications. However, there is an increasing demand for wideband speech applications in order to increase the intelligibility and naturalness of the speech signals. A bandwidth in the range 50-7000 Hz was found sufficient for delivering a face-to-face speech quality. For audio signals, this range gives an acceptable audio quality, but still lower than the CD quality which operates on the range 20-20000 Hz.

[0003] A speech encoder converts a speech signal into a digital bitstream which is transmitted over a communication channel (or stored in a storage medium). The speech signal is digitized (sampled and quantized with usually 16-bits per sample) and the speech encoder has the role of representing these digital samples with a smaller number of bits while maintaining a good subjective speech quality. The speech decoder or synthesizer operates on the transmitted or stored bit stream and converts it back to a sound signal.

[0004] In the prior art, document US-A-5 455 888 discloses a speech bandwidth extension scheme using LPC analysis.

[0005] One of the best prior art techniques capable of achieving a good quality/bit rate trade-off is the so-called Code Excited Linear Prediction (CELP) technique. According to this technique, the sampled speech signal is processed in successive blocks of L samples usually called *frames* where L is some predetermined number (corresponding to 10-30 ms of speech). In CELP, a linear prediction (LP) synthesis filter is computed and transmitted every frame. The L -sample frame is then divided into smaller blocks called *subframes* of size of N samples, where $L=kN$ and k is the number of subframes in a frame (N usually corresponds to 4-10 ms of speech). An excitation signal is determined in each subframe, which usually consists of two components: one from the past excitation (also called pitch contribution or adaptive codebook) and the other from an innovative codebook (also called fixed codebook). This excitation signal is transmitted and used at the decoder as the input of the LP synthesis filter in order to obtain the synthesized speech.

[0006] An innovative codebook in the CELP context, is an indexed set of N -sample-long sequences which will be referred to as N -dimensional codevectors. Each codebook sequence is indexed by an integer k ranging from 1 to M where M represents the size of the codebook often expressed as a number of bits b , where $M=2^b$.

[0007] To synthesize speech according to the CELP technique, each block of N samples is synthesized by filtering an appropriate codevector from a codebook through time varying filters modeling the spectral characteristics of the speech signal. At the encoder end, the synthesis output is computed for all, or a subset, of the codevectors from the codebook (codebook search). The retained codevector is the one producing the synthesis output closest to the original speech signal according to a perceptually weighted distortion measure. This perceptual weighting is performed using a so-called perceptual weighting filter, which is usually derived from the LP synthesis filter.

[0008] The CELP model has been very successful in encoding telephone band sound signals, and several CELP-based standards exist in a wide range of applications, especially in digital cellular applications. In the telephone band, the sound signal is band-limited to 200-3400 Hz and sampled at 8000 samples/sec. In wideband speech/audio applications, the sound signal is band-limited to 50-7000 Hz and sampled at 16000 samples/sec.

[0009] Some difficulties arise when applying the telephone-band optimized CELP model to wideband signals, and additional features need to be added to the model in order to obtain high quality wideband signals. Wideband signals exhibit a much wider dynamic range compared to telephone-band signals, which results in precision problems when a fixed-point implementation of the algorithm is required (which is essential in wireless applications). Further, the CELP model will often spend most of its encoding bits on the low-frequency region, which usually has higher energy contents, resulting in a low-pass output signal. To overcome this problem, the perceptual weighting filter has to be modified in order to suit wideband signals, and pre-emphasis techniques which boost the high frequency regions become important to reduce the dynamic range, yielding a simpler fixed-point implementation, and to ensure a better encoding of the higher frequency contents of the signal. Further, the pitch contents in the spectrum of voiced segments in wideband signals do not extend over the whole spectrum range, and the amount of voicing shows more variation compared to

narrow-band signals. Thus, it is important to improve the closed-loop pitch analysis to better accommodate the variations in the voicing level.

[0010] Some difficulties arise when applying the telephone-band optimized CELP model to wideband signals, and additional features need to be added to the model in order to obtain high quality wideband signals.

5 [0011] As an example, in order to improve the coding efficiency and reduce the algorithmic complexity of the wideband encoding algorithm, the input wideband signal is down-sampled from 16 kHz to around 12.8 kHz. This reduces the number of samples in a frame, the processing time and the signal bandwidth below 7000 Hz to thereby enable reduction in bit rate down to 12 kbit/s while keeping very high quality decoded sound signal. The complexity is also reduced due to the lower number of samples per speech frame. At the decoder, the high frequency contents of the signal needs to be reintroduced to remove the low pass filtering effect from the decoded synthesized signal and retrieve the natural sounding quality of wideband signals. For that purpose, an efficient technique for recovering the high frequency content of the wideband signal is needed to thereby produce a full-spectrum wideband synthesized signal, while maintaining a quality close to the original signal.

10 15 OBJECT OF THE INVENTION

[0012] An object of the present invention is therefore to provide such an efficient high frequency content recovery technique.

20 25 SUMMARY OF THE INVENTION

[0013] More specifically, in accordance with the present invention, there is provided a method for recovering a high frequency content of a wideband signal previously down-sampled and for injecting the high frequency content in an over-sampled synthesized version of the wideband signal to produce a full-spectrum synthesized wideband signal.

25 30 This high-frequency content recovering method comprises: generating a noise sequence; spectrally-shaping the noise sequence in relation to shaping parameters representative of the down-sampled wideband signal; and injecting the spectrally-shaped noise sequence in the over-sampled synthesized signal version to thereby produce the full-spectrum synthesized wideband signal.

[0014] The present invention further relates to a device for recovering a high frequency content of a wideband signal previously down-sampled and for injecting this high frequency content in an over-sampled synthesized version of the wideband signal to produce a full-spectrum synthesized wideband signal. This high-frequency content recovering device comprises a noise generator for producing a noise sequence, a spectral shaping unit for shaping the noise sequence in relation to shaping parameters representative of the down-sampled wideband signal, and a signal injection circuit for injecting the spectrally-shaped noise sequence in the over-sampled synthesized signal version to thereby produce the full-spectrum synthesized wideband signal.

35 [0015] In accordance with a preferred embodiment, the noise sequence is a white noise sequence.

[0016] Preferably, spectral shaping of the noise sequence comprises:

40 45 producing a scaled white noise sequence in response to the white noise sequence and a first subset of the shaping parameters; filtering the scaled white noise sequence in relation to a second subset of the shaping parameters comprising bandwidth expanded synthesis filter coefficients to produce a filtered scaled white noise sequence characterized by a frequency bandwidth generally higher than a frequency bandwidth of the over-sampled synthesized signal version; and band-pass filtering the filtered scaled white noise sequence to produce a band-pass filtered scaled white noise sequence to be subsequently injected in the over-sampled synthesized signal version as the spectrally-shaped white noise sequence.

[0017] Still according to the present invention, there is provided a decoder for producing a synthesized wideband signal, comprising:

- 50 a) a signal fragmenting device for receiving an encoded version of a wideband signal previously down-sampled during encoding and extracting from the encoded wideband signal version at least pitch codebook parameters, innovative codebook parameters, and synthesis filter coefficients;
- b) a pitch codebook responsive to the pitch codebook parameters for producing a pitch codevector;
- c) an innovative codebook responsive to the innovative codebook parameters for producing an innovative codevector;
- d) a combiner circuit for combining the pitch codevector and the innovative codevector to thereby produce an excitation signal;
- e) a signal synthesis device including a synthesis filter for filtering the excitation signal in relation to the synthesis

filter coefficients to thereby produce a synthesized wideband signal, and an oversampler responsive to the synthesized wideband signal for producing an over-sampled signal version of the synthesized wideband signal; and f) a high-frequency content recovering device as described hereinabove, for recovering a high frequency content of the wideband signal and for injecting the high frequency content in the over-sampled signal version to produce the full-spectrum synthesized wideband signal.

[0018] In accordance with a preferred embodiment, the decoder further comprises:

- a) a voicing factor generator responsive to the adaptive and innovative codevectors for calculating a voicing factor for forwarding to the gain adjustment module;
- b) an energy computing module responsive to the excitation signal for calculating an excitation energy for forwarding to the gain adjustment module; and
- c) a spectral tilt calculator responsive to the synthesized signal for calculating a tilt scaling factor for forwarding to the gain adjustment module. The first subset of the shaping parameters comprises the voicing factor, the energy scaling factor, and the tilt scaling factor, and the second subset of the shaping parameters includes linear prediction coefficients.

[0019] In accordance with other preferred embodiments of the decoder:

- the voicing factor generator calculates the voicing factor r_v using the relation:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

where E_v is the energy of the gain scaled pitch codevector and E_c is the energy of the gain scaled innovative codevector;

- the gain adjusting unit calculates an energy scaling factor using the relation:

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N'-1} w'^2(n)}}, \quad n=0, \dots, N'-1.$$

where w' is the white noise sequence and u' is an enhanced excitation signal derived from the excitation signal;

- the spectral tilt calculator calculates the tilt scaling factor g_t using the relation:

$$g_t = 1 - \text{tilt}$$

bounded by $0.2 \leq g_t \leq 1.0$

where

5

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

- 10 conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$
or the relation:

$$g_t = 10^{-0.6 \text{tilt}}$$

15

bounded by $0.2 \leq g_t \leq 1.0$
where

20

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

30

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

[0020] Preferably, the band-pass filter has a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

[0021] Also according to the present invention, in a decoder for producing a synthesized wideband signal, comprising:

35

- a) a signal fragmenting device for receiving an encoded version of a wideband signal previously down-sampled during encoding and extracting from the encoded wideband signal version at least pitch codebook parameters, innovative codebook parameters, and synthesis filter coefficients;
 - b) a pitch codebook responsive to the pitch codebook parameters for producing a pitch codevector;
 - c) an innovative codebook responsive to the innovative codebook parameters for producing an innovative codevector;
 - d) a combiner circuit for combining the pitch codevector and the innovative codevector to thereby produce an excitation signal; and
 - e) a signal synthesis device including a synthesis filter for filtering the excitation signal in relation to the synthesis filter coefficients to thereby produce a synthesized wideband signal, and an oversampler responsive to the synthesized wideband signal for producing an over-sampled signal version of the synthesized wideband signal;
- the improvement comprising a high-frequency content recovering device as described hereinabove for recovering a high frequency content of the wideband signal and for injecting the high frequency content in the over-sampled signal version to produce the full-spectrum synthesized wideband signal.

40

50

[0022] The present invention finally comprises a cellular communication system, a cellular mobile transmitter/receiver unit, a cellular network element, and a bidirectional wireless communication sub-system comprising the above described decoder.

[0023] The objects, advantages and other features of the present invention will become more apparent upon reading of the following non restrictive description of a preferred embodiment thereof, given by way of example only with reference to the accompanying drawings.

55 BRIEF DESCRIPTION OF THE DRAWINGS

[0024] In the appended drawings:

Figure 1 is a schematic block diagram of a preferred embodiment of wideband encoding device;

Figure 2 is a schematic block diagram of a preferred embodiment of wideband decoding device;

5 Figure 3 is a schematic block diagram of a preferred embodiment of pitch analysis device; and

Figure 4 is a simplified, schematic block diagram of a cellular communication system in which the wideband encoding device of Figure 1 and the wideband decoding device of Figure 2 can be used.

10 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0025] As well known to those of ordinary skill in the art, a cellular communication system such as 401 (see Figure 4) provides a telecommunication service over a large geographic area by dividing that large geographic area into a number C of smaller cells. The C smaller cells are serviced by respective cellular base stations 402₁, 402₂ ... 402_C to provide each cell with radio signalling, audio and data channels.

[0026] Radio signalling channels are used to page mobile radiotelephones (mobile transmitter/receiver units) such as 403 within the limits of the coverage area (cell) of the cellular base station 402, and to place calls to other radiotelephones 403 located either inside or outside the base station's cell or to another network such as the Public Switched Telephone Network (PSTN) 404.

[0027] Once a radiotelephone 403 has successfully placed or received a call, an audio or data channel is established between this radiotelephone 403 and the cellular base station 402 corresponding to the cell in which the radiotelephone 403 is situated, and communication between the base station 402 and radiotelephone 403 is conducted over that audio or data channel. The radiotelephone 403 may also receive control or timing information over a signalling channel while a call is in progress.

[0028] If a radiotelephone 403 leaves a cell and enters another adjacent cell while a call is in progress, the radiotelephone 403 hands over the call to an available audio or data channel of the new cell base station 402. If a radiotelephone 403 leaves a cell and enters another adjacent cell while no call is in progress, the radiotelephone 403 sends a control message over the signalling channel to log into the base station 402 of the new cell. In this manner mobile communication over a wide geographical area is possible.

[0029] The cellular communication system 401 further comprises a control terminal 405 to control communication between the cellular base stations 402 and the PSTN 404, for example during a communication between a radiotelephone 403 and the PSTN 404, or between a radiotelephone 403 located in a first cell and a radiotelephone 403 situated in a second cell.

[0030] Of course, a bidirectional wireless radio communication subsystem is required to establish an audio or data channel between a base station 402 of one cell and a radiotelephone 403 located in that cell. As illustrated in very simplified form in Figure 4, such a bidirectional wireless radio communication subsystem typically comprises in the radiotelephone 403:

- a transmitter 406 including:
 - an encoder 407 for encoding the voice signal; and
 - a transmission circuit 408 for transmitting the encoded voice signal from the encoder 407 through an antenna such as 409; and
- a receiver 410 including:
 - a receiving circuit 411 for receiving a transmitted encoded voice signal usually through the same antenna 409; and
 - a decoder 412 for decoding the received encoded voice signal from the receiving circuit 411.

[0031] The radiotelephone further comprises other conventional radiotelephone circuits 413 to which the encoder 407 and decoder 412 are connected and for processing signals therefrom, which circuits 413 are well known to those of ordinary skill in the art and, accordingly, will not be further described in the present specification.

[0032] Also, such a bidirectional wireless radio communication subsystem typically comprises in the base station 402:

- a transmitter 414 including:
 - an encoder 415 for encoding the voice signal; and

- a transmission circuit 416 for transmitting the encoded voice signal from the encoder 415 through an antenna such as 417; and
- a receiver 418 including:

- 5
- a receiving circuit 419 for receiving a transmitted encoded voice signal through the same antenna 417 or through another antenna (not shown); and
 - a decoder 420 for decoding the received encoded voice signal from the receiving circuit 419.

10 [0033] The base station 402 further comprises, typically, a base station controller 421, along with its associated database 422, for controlling communication between the control terminal 405 and the transmitter 414 and receiver 418.

[0034] As well known to those of ordinary skill in the art, voice encoding is required in order to reduce the bandwidth necessary to transmit sound signal, for example voice signal such as speech, across the bidirectional wireless radio communication subsystem, i.e., between a radiotelephone 403 and a base station 402.

15 [0035] LP voice encoders (such as 415 and 407) typically operating at 13 kbits/second and below such as Code-Excited Linear Prediction (CELP) encoders typically use a LP synthesis filter to model the short-term spectral envelope of the voice signal. The LP information is transmitted, typically, every 10 or 20 ms to the decoder (such 420 and 412) and is extracted at the decoder end.

[0036] The novel techniques disclosed in the present specification may apply to different LP-based coding systems. 20 However, a CELP-type coding system is used in the preferred embodiment for the purpose of presenting a non-limitative illustration of these techniques. In the same manner, such techniques can be used with sound signals other than voice and speech as well with other types of wideband signals.

[0037] Figure 1 shows a general block diagram of a CELP-type speech encoding device 100 modified to better accommodate wideband signals.

25 [0038] The sampled input speech signal 114 is divided into successive L -sample blocks called "frames". In each frame, different parameters representing the speech signal in the frame are computed, encoded, and transmitted. LP parameters representing the LP synthesis filter are usually computed once every frame. The frame is further divided into smaller blocks of N samples (blocks of length N), in which excitation parameters (pitch and innovation) are determined. In the CELP literature, these blocks of length N are called "subframes" and the N -sample signals in the subframes are referred to as N -dimensional vectors. In this preferred embodiment, the length N corresponds to 5 ms while the length L corresponds to 20 ms, which means that a frame contains four subframes ($N=80$ at the sampling rate of 16 kHz and 64 after down-sampling to 12.8 kHz). Various N dimensional vectors occur in the encoding procedure. A list of the vectors which appear in Figures 1 and 2 as well as a list of transmitted parameters are given herein below:

35 List of the main N -dimensional vectors

[0039]

- s Wideband signal input speech vector (after down-sampling, pre-processing, and preemphasis);
- s_w Weighted speech vector;
- s_o Zero-input response of weighted synthesis filter;
- s_p Down-sampled pre-processed signal;
- s' Oversampled synthesized speech signal;
- s' Synthesis signal before deemphasis;
- s_d Deemphasized synthesis signal;
- s_h Synthesis signal after deemphasis and postprocessing;
- x Target vector for pitch search;
- x' Target vector for innovation search;
- h Weighted synthesis filter impulse response;
- v_T Adaptive (pitch) codebook vector at delay T ;
- y_T Filtered pitch codebook vector (v_T convolved with h);
- c_k Innovative codevector at index k (k -th entry from the innovation codebook);
- c_f Enhanced scaled innovation codevector;
- u Excitation signal (scaled innovation and pitch codevectors);
- u' Enhanced excitation;
- z Band-pass noise sequence;
- w' White noise sequence; and
- w Scaled noise sequence.

List of transmitted parameters**[0040]**

- 5 STP Short term prediction parameters (defining $A(z)$);
 T Pitch lag (or pitch codebook index);
 b Pitch gain (or pitch codebook gain);
 j Index of the low-pass filter used on the pitch codevector;
 k Codevector index (innovation codebook entry); and
10 g Innovation codebook gain.

[0041] In this preferred embodiment, the STP parameters are transmitted once per frame and the rest of the parameters are transmitted four times per frame (every subframe).

15 ENCODER SIDE

[0042] The sampled speech signal is encoded on a block by block basis by the encoding device 100 of Figure 1 which is broken down into eleven modules numbered from 101 to 111.

[0043] The input speech is processed into the above mentioned L-sample blocks called frames.

20 **[0044]** Referring to Figure 1, the sampled input speech signal 114 is down-sampled in a down-sampling module 101. For example, the signal is down-sampled from 16 kHz down to 12.8 kHz, using techniques well known to those of ordinary skill in the art. Down-sampling down to another frequency can of course be envisaged. Down-sampling increases the coding efficiency, since a smaller frequency bandwidth is encoded. This also reduces the algorithmic complexity since the number of samples in a frame is decreased. The use of down-sampling becomes significant when 25 the bit rate is reduced below 16 kbit/s, although down-sampling is not essential above 16 kbit/s.

[0045] After down-sampling, the 320-sample frame of 20 ms is reduced to 256-sample frame (down-sampling ratio of 4/5).

30 **[0046]** The input frame is then supplied to the optional pre-processing block 102. Pre-processing block 102 may consist of a high-pass filter with a 50 Hz cut-off frequency. High-pass filter 102 removes the unwanted sound components below 50 Hz.

[0047] The down-sampled pre-processed signal is denoted by $s_p(n)$, $n=0, 1, 2, \dots, L-1$, where L is the length of the frame (256 at a sampling frequency of 12.8 kHz). In a preferred embodiment of the preemphasis filter 103, the signal $s_p(n)$ is preemphasized using a filter having the following transfer function:

35
$$P(z) = 1 - \mu z^{-1}$$

where μ is a preemphasis factor with a value located between 0 and 1 (a typical value is $\mu = 0.7$). A higher-order filter could also be used. It should be pointed out that high-pass filter 102 and preemphasis filter 103 can be interchanged to obtain more efficient fixed-point implementations.

[0048] The function of the preemphasis filter 103 is to enhance the high frequency contents of the input signal. It also reduces the dynamic range of the input speech signal, which renders it more suitable for fixed-point implementation. Without preemphasis, LP analysis in fixed-point using single-precision arithmetic is difficult to implement.

[0049] Preemphasis also plays an important role in achieving a proper overall perceptual weighting of the quantization error, which contributes to improved sound quality. This will be explained in more detail herein below.

50 **[0050]** The output of the preemphasis filter 103 is denoted $s(n)$. This signal is used for performing LP analysis in calculator module 104. LP analysis is a technique well known to those of ordinary skill in the art. In this preferred embodiment, the autocorrelation approach is used. In the autocorrelation approach, the signal $s(n)$ is first windowed using a Hamming window (having usually a length of the order of 30-40 ms). The autocorrelations are computed from the windowed signal, and Levinson-Durbin recursion is used to compute LP filter coefficients, a_i , where $i=1, \dots, p$, and where p is the LP order, which is typically 16 in wideband coding. The parameters a_i are the coefficients of the transfer function of the LP filter, which is given by the following relation:

$$A(z) = 1 + \sum_{l=1}^P a_l z^{-l}$$

5

[0051] LP analysis is performed in calculator module 104, which also performs the quantization and interpolation of the LP filter coefficients. The LP filter coefficients are first transformed into another equivalent domain more suitable for quantization and interpolation purposes. The line spectral pair (LSP) and immittance spectral pair (ISP) domains are two domains in which quantization and interpolation can be efficiently performed. The 16 LP filter coefficients, a_i , can be quantized in the order of 30 to 50 bits using split or multi-stage quantization, or a combination thereof. The purpose of the interpolation is to enable updating the LP filter coefficients every subframe while transmitting them once every frame, which improves the encoder performance without increasing the bit rate. Quantization and interpolation of the LP filter coefficients is believed to be otherwise well known to those of ordinary skill in the art and, accordingly, will not be further described in the present specification.

[0052] The following paragraphs will describe the rest of the coding operations performed on a subframe basis. In the following description, the filter $A(z)$ denotes the unquantized interpolated LP filter of the subframe, and the filter $\hat{A}(z)$ denotes the quantized interpolated LP filter of the subframe.

20

Perceptual Weighting:

[0053] In analysis-by-synthesis encoders, the optimum pitch and innovation parameters are searched by minimizing the mean squared error between the input speech and synthesized speech in a perceptually weighted domain. This is equivalent to minimizing the error between the weighted input speech and weighted synthesis speech.

[0054] The weighted signal $s_w(n)$ is computed in a perceptual weighting filter 105. Traditionally, the weighted signal $s_w(n)$ is computed by a weighting filter having a transfer function $W(z)$ in the form:

$$W(z) = A(z/\gamma_1) / A(z/\gamma_2)$$

30 where $0 < \gamma_2 < \gamma_1 \leq 1$

As well known to those of ordinary skill in the art, in prior art analysis-by-synthesis (AbS) encoders, analysis shows that the quantization error is weighted by a transfer function $W^{-1}(z)$, which is the inverse of the transfer function of the perceptual weighting filter 105. This result is well described by B.S. Atal and M.R. Schroeder in "Predictive coding of speech and subjective error criteria", IEEE Transaction ASSP, vol. 27, no. 3, pp. 247-254, June 1979. Transfer function $W^{-1}(z)$ exhibits some of the formant structure of the input speech signal. Thus, the masking property of the human ear is exploited by shaping the quantization error so that it has more energy in the formant regions where it will be masked by the strong signal energy present in these regions. The amount of weighting is controlled by the factors γ_1 and γ_2 .

[0055] The above traditional perceptual weighting filter 105 works well with telephone band signals. However, it was found that this traditional perceptual weighting filter 105 is not suitable for efficient perceptual weighting of wideband signals. It was also found that the traditional perceptual weighting filter 105 has inherent limitations in modelling the formant structure and the required spectral tilt concurrently. The spectral tilt is more pronounced in wideband signals due to the wide dynamic range between low and high frequencies. The prior art has suggested to add a tilt filter into $W(z)$ in order to control the tilt and formant weighting of the wideband input signal separately.

[0056] A novel solution to this problem is, in accordance with the present invention, to introduce the preemphasis filter 103 at the input, compute the LP filter $A(z)$ based on the preemphasized speech $s(n)$, and use a modified filter $W(z)$ by fixing its denominator.

[0057] LP analysis is performed in module 104 on the preemphasized signal $s(n)$ to obtain the LP filter $A(z)$. Also, a new perceptual weighting filter 105 with fixed denominator is used. An example of transfer function for the perceptual weighting filter 104 is given by the following relation:

$$W(z) = A(z/\gamma_1) / (1 - \gamma_2 z^{-1})$$

55

where $0 < \gamma_2 < \gamma_1 \leq 1$

A higher order can be used at the denominator. This structure substantially decouples the formant weighting from the tilt.

[0058] Note that because $A(z)$ is computed based on the preemphasized speech signal $s(n)$, the tilt of the filter $1/A$

(z/γ_1) is less pronounced compared to the case when $A(z)$ is computed based on the original speech. Since deemphasis is performed at the decoder end using a filter having the transfer function:

$$P^{-1}(z) = 1/(1-\mu z^{-1}),$$

the quantization error spectrum is shaped by a filter having a transfer function $W^{-1}(z)P^{-1}(z)$. When γ_2 is set equal to μ , which is typically the case, the spectrum of the quantization error is shaped by a filter whose transfer function is $1/A(z/\gamma_1)$, with $A(z)$ computed based on the preemphasized speech signal. Subjective listening showed that this structure for achieving the error shaping by a combination of preemphasis and modified weighting filtering is very efficient for encoding wideband signals, in addition to the advantages of ease of fixed-point algorithmic implementation.

Pitch Analysis:

[0059] In order to simplify the pitch analysis, an open-loop pitch lag T_{OL} is first estimated in the open-loop pitch search module 106 using the weighted speech signal $s_w(n)$. Then the closed-loop pitch analysis, which is performed in closed-loop pitch search module 107 on a subframe basis, is restricted around the open-loop pitch lag T_{OL} which significantly reduces the search complexity of the LTP parameters T and b (pitch lag and pitch gain). Open-loop pitch analysis is usually performed in module 106 once every 10 ms (two subframes) using techniques well known to those of ordinary skill in the art.

[0060] The target vector \mathbf{x} for LTP (Long Term Prediction) analysis is first computed. This is usually done by subtracting the zero-input response \mathbf{s}_0 of weighted synthesis filter $W(z)/\hat{A}(z)$ from the weighted speech signal $s_w(n)$. This zero-input response \mathbf{s}_0 is calculated by a zero-input response calculator 108. More specifically, the target vector \mathbf{x} is calculated using the following relation:

$$\mathbf{x} = \mathbf{s}_w - \mathbf{s}_0$$

where \mathbf{x} is the N -dimensional target vector, \mathbf{s}_w is the weighted speech vector in the subframe, and \mathbf{s}_0 is the zero-input response of filter $W(z)/\hat{A}(z)$ which is the output of the combined filter $W(z)/\hat{A}(z)$ due to its initial states. The zero-input response calculator 108 is responsive to the quantized interpolated LP filter $\hat{A}(z)$ from the LP analysis, quantization and interpolation calculator 104 and to the initial states of the weighted synthesis filter $W(z)/\hat{A}(z)$ stored in memory module 111 to calculate the zero-input response \mathbf{s}_0 (that part of the response due to the initial states as determined by setting the inputs equal to zero) of filter $W(z)/\hat{A}(z)$. This operation is well known to those of ordinary skill in the art and, accordingly, will not be further described.

[0061] Of course, alternative but mathematically equivalent approaches can be used to compute the target vector \mathbf{x} .

[0062] A N -dimensional impulse response vector \mathbf{h} of the weighted synthesis filter $W(z)/\hat{A}(z)$ is computed in the impulse response generator 109 using the LP filter coefficients $A(z)$ and $\hat{A}(z)$ from module 104. Again, this operation is well known to those of ordinary skill in the art and, accordingly, will not be further described in the present specification.

[0063] The closed-loop pitch (or pitch codebook) parameters b , T and j are computed in the closed-loop pitch search module 107, which uses the target vector \mathbf{x} , the impulse response vector \mathbf{h} and the open-loop pitch lag T_{OL} as inputs. Traditionally, the pitch prediction has been represented by a pitch filter having the following transfer function:

$$1 / (1 - bz^{-T})$$

where b is the pitch gain and T is the pitch delay or lag. In this case, the pitch contribution to the excitation signal $u(n)$ is given by $bu(n-T)$, where the total excitation is given by

$$u(n) = bu(n-T) + gc_k(n)$$

with g being the innovative codebook gain and $c_k(n)$ the innovative codevector at index k .

[0064] This representation has limitations if the pitch lag T is shorter than the subframe length N . In another representation, the pitch contribution can be seen as a pitch codebook containing the past excitation signal. Generally, each vector in the pitch codebook is a shift-by-one version of the previous vector (discarding one sample and adding a new sample). For pitch lags $T > N$, the pitch codebook is equivalent to the filter structure $(1/(1-bz^T))$, and a pitch codebook vector $v_T(n)$ at pitch lag T is given by

$$v_T(n) = u(n-T),$$

n=0,...,N-1.

- 5 For pitch lags T shorter than N , a vector $v_T(n)$ is built by repeating the available samples from the past excitation until the vector is completed (this is not equivalent to the filter structure).

[0065] In recent encoders, a higher pitch resolution is used which significantly improves the quality of voiced sound segments. This is achieved by oversampling the past excitation signal using polyphase interpolation filters. In this case, the vector $v_T(n)$ usually corresponds to an interpolated version of the past excitation, with pitch lag T being a non-integer delay (e.g. 50.25).

[0066] The pitch search consists of finding the best pitch lag T and gain b that minimize the mean squared weighted error E between the target vector x and the scaled filtered past excitation. Error E being expressed as:

$$15 \quad E = \|x - b y_T\|^2$$

where y_T is the filtered pitch codebook vector at pitch lag T :

$$20 \quad y_T(n) = v_T(n) * h(n) = \sum_{i=0}^n v_T(i)h(n-i), \quad n=0,...,N-1.$$

25 It can be shown that the error E is minimized by maximizing the search criterion

$$30 \quad C = \frac{x^t y_T}{\sqrt{y_T^t y_T}}$$

where t denotes vector transpose.

[0067] In the preferred embodiment of the present invention, a 1/3 subsample pitch resolution is used, and the pitch (pitch codebook) search is composed of three stages.

[0068] In the first stage, an open-loop pitch lag T_{OL} is estimated in open-loop pitch search module 106 in response to the weighted speech signal $s_w(n)$. As indicated in the foregoing description, this open-loop pitch analysis is usually performed once every 10 ms (two subframes) using techniques well known to those of ordinary skill in the art.

[0069] In the second stage, the search criterion C is searched in the closed-loop pitch search module 107 for integer pitch lags around the estimated open-loop pitch lag T_{OL} (usually ± 5), which significantly simplifies the search procedure. A simple procedure is used for updating the filtered codevector y_T without the need to compute the convolution for every pitch lag.

[0070] Once an optimum integer pitch lag is found in the second stage, a third stage of the search (module 107) tests the fractions around that optimum integer pitch lag.

[0071] When the pitch predictor is represented by a filter of the form $1/(1-bz^{-T})$, which is a valid assumption for pitch lags $T > N$, the spectrum of the pitch filter exhibits a harmonic structure over the entire frequency range, with a harmonic frequency related to $1/T$. In case of wideband signals, this structure is not very efficient since the harmonic structure in wideband signals does not cover the entire extended spectrum. The harmonic structure exists only up to a certain frequency, depending on the speech segment. Thus, in order to achieve efficient representation of the pitch contribution in voiced segments of wideband speech, the pitch prediction filter needs to have the flexibility of varying the amount of periodicity over the wideband spectrum.

[0072] A new method which achieves efficient modeling of the harmonic structure of the speech spectrum of wideband signals is disclosed in the present specification, whereby several forms of low pass filters are applied to the past excitation and the low pass filter with higher prediction gain is selected.

[0073] When subsample pitch resolution is used, the low pass filters can be incorporated into the interpolation filters used to obtain the higher pitch resolution. In this case, the third stage of the pitch search, in which the fractions around the chosen integer pitch lag are tested, is repeated for the several interpolation filters having different low-pass characteristics and the fraction and filter index which maximize the search criterion C are selected.

[0074] A simpler approach is to complete the search in the three stages described above to determine the optimum fractional pitch lag using only one interpolation filter with a certain frequency response, and select the optimum low-pass filter shape at the end by applying the different predetermined low-pass filters to the chosen pitch codebook vector \mathbf{v}_T and select the low-pass filter which minimizes the pitch prediction error. This approach is discussed in detail below.

5 **[0075]** Figure 3 illustrates a schematic block diagram of a preferred embodiment of the proposed approach.

[0076] In memory module 303, the past excitation signal $u(n)$, $n < 0$, is stored. The pitch codebook search module 301 is responsive to the target vector \mathbf{x} , to the open-loop pitch lag T_{OL} and to the past excitation signal $u(n)$, $n < 0$, from memory module 303 to conduct a pitch codebook (pitch codebook) search minimizing the above-defined search criterion C. From the result of the search conducted in module 301, module 302 generates the optimum pitch codebook vector \mathbf{v}_T . Note that since a sub-sample pitch resolution is used (fractional pitch), the past excitation signal $u(n)$, $n < 0$, is interpolated and the pitch codebook vector \mathbf{v}_T corresponds to the interpolated past excitation signal. In this preferred embodiment, the interpolation filter (in module 301, but not shown) has a low-pass filter characteristic removing the frequency contents above 7000 Hz.

10 **[0077]** In a preferred embodiment, K filter characteristics are used; these filter characteristics could be low-pass or band-pass filter characteristics. Once the optimum codevector \mathbf{v}_T is determined and supplied by the pitch codevector generator 302, K filtered versions of \mathbf{v}_T are computed respectively using K different frequency shaping filters such as 305 $^{(j)}$, where $j = 1, 2, \dots, K$. These filtered versions are denoted $\mathbf{v}_{T,f}^{(j)}$, where $j = 1, 2, \dots, K$. The different vectors $\mathbf{v}_{T,f}^{(j)}$ are convolved in respective modules 304 $^{(j)}$, where $j = 0, 1, 2, \dots, K$, with the impulse response \mathbf{h} to obtain the vectors $\mathbf{y}^{(j)}$, where $j = 0, 1, 2, \dots, K$. To calculate the mean squared pitch prediction error for each vector $\mathbf{y}^{(j)}$, the value $\mathbf{y}^{(j)}$ is multiplied by the gain b by means of a corresponding amplifier 307 $^{(j)}$ and the value $b\mathbf{y}^{(j)}$ is subtracted from the target vector \mathbf{x} by means of a corresponding subtractor 308 $^{(j)}$. Selector 309 selects the frequency shaping filter 305 $^{(j)}$ which minimizes the mean squared pitch prediction error

$$25 e^{(j)} = \| \mathbf{x} - b^{(j)} \mathbf{y}^{(j)} \|^2,$$

$j = 1, 2, \dots, K$

To calculate the mean squared pitch prediction error $e^{(j)}$ for each value of $\mathbf{y}^{(j)}$, the value $\mathbf{y}^{(j)}$ is multiplied by the gain b by means of a corresponding amplifier 307 $^{(j)}$ and the value $b^{(j)}\mathbf{y}^{(j)}$ is subtracted from the target vector \mathbf{x} by means of subtractors 308 $^{(j)}$. Each gain $b^{(j)}$ is calculated in a corresponding gain calculator 306 $^{(j)}$ in association with the frequency shaping filter at index j , using the following relationship:

$$b^{(j)} = \mathbf{x}^T \mathbf{y}^{(j)} / \|\mathbf{y}^{(j)}\|^2$$

35

[0078] In selector 309, the parameters b , T , and j are chosen based on \mathbf{v}_T or $\mathbf{v}_{T,f}^{(j)}$, which minimizes the mean squared pitch prediction error e .

[0079] Referring back to Figure 1, the pitch codebook index T is encoded and transmitted to multiplexer 112. The pitch gain b is quantized and transmitted to multiplexer 112. With this new approach, extra information is needed to encode the index j of the selected frequency shaping filter in multiplexer 112. For example, if three filters are used ($j = 0, 1, 2, 3$), then two bits are needed to represent this information. The filter index information j can also be encoded jointly with the pitch gain b .

Innovative codebook search:

45

[0080] Once the pitch, or LTP (Long Term Prediction) parameters b , T , and j are determined, the next step is to search for the optimum innovative excitation by means of search module 110 of Figure 1. First, the target vector \mathbf{x} is updated by subtracting the LTP contribution:

50

$$\mathbf{x}' = \mathbf{x} - b\mathbf{y}_T$$

where b is the pitch gain and \mathbf{y}_T is the filtered pitch codebook vector (the past excitation at delay T filtered with the selected low pass filter and convolved with the impulse response \mathbf{h} as described with reference to Figure 3).

55 **[0081]** The search procedure in CELP is performed by finding the optimum excitation codevector \mathbf{c}_k and gain g which minimize the mean-squared error between the target vector and the scaled filtered codevector

$$E = \| \mathbf{x}' - gH\mathbf{c}_k \|^2$$

where H is a lower triangular convolution matrix derived from the impulse response vector \mathbf{h} .

[0082] In the preferred embodiment of the present invention, the innovative codebook search is performed in module 110 by means of an algebraic codebook as described in US patents Nos: 5,444,816 (Adoul et al.) issued on August 22, 1995; 5,699,482 granted to Adoul et al., on December 17, 1997; 5,754,976 granted to Adoul et al., on May 19, 1998; and 5,701,392 (Adoul et al.) dated December 23, 1997.

[0083] Once the optimum excitation codevector \mathbf{c}_k and its gain g are chosen by module 110, the codebook index k and gain g are encoded and transmitted to multiplexer 112.

[0084] Referring to Figure 1, the parameters b , T , j , $\hat{A}(z)$, k and g are multiplexed through the multiplexer 112 before being transmitted through a communication channel.

Memory update:

[0085] In memory module 111 (Figure 1), the states of the weighted synthesis filter $W(z)/\hat{A}(z)$ are updated by filtering the excitation signal $\mathbf{u} = g\mathbf{c}_k + b\mathbf{v}_T$ through the weighted synthesis filter. After this filtering, the states of the filter are memorized and used in the next subframe as initial states for computing the zero-input response in calculator module 108.

[0086] As in the case of the target vector \mathbf{x} , other alternative but mathematically equivalent approaches well known to those of ordinary skill in the art can be used to update the filter states.

DECODER SIDE

[0087] The speech decoding device 200 of Figure 2 illustrates the various steps carried out between the digital input 222 (input stream to the demultiplexer 217) and the output sampled speech 223 (output of the adder 221).

[0088] Demultiplexer 217 extracts the synthesis model parameters from the binary information received from a digital input channel. From each received binary frame, the extracted parameters are:

- the short-term prediction parameters (STP) $\hat{A}(z)$ (once per frame);
- the long-term prediction (LTP) parameters T , b , and j (for each subframe); and
- the innovation codebook index k and gain g (for each subframe).

The current speech signal is synthesized based on these parameters as will be explained hereinbelow.

[0089] The innovative codebook 218 is responsive to the index k to produce the innovation codevector \mathbf{c}_k , which is scaled by the decoded gain factor g through an amplifier 224. In the preferred embodiment, an innovative codebook 218 as described in the above mentioned US patent numbers 5,444,816; 5,699,482; 5,754,976; and 5,701,392 is used to represent the innovative codevector \mathbf{c}_k .

[0090] The generated scaled codevector $g\mathbf{c}_k$ at the output of the amplifier 224 is processed through a innovation filter 205.

Periodicity enhancement

[0091] The generated scaled codevector at the output of the amplifier 224 is processed through a frequency-dependent pitch enhancer 205.

[0092] Enhancing the periodicity of the excitation signal \mathbf{u} improves the quality in case of voiced segments. This was done in the past by filtering the innovation vector from the innovative codebook (fixed codebook) 218 through a filter in the form $1/(1-\epsilon bz^{-T})$ where ϵ is a factor below 0.5 which controls the amount of introduced periodicity. This approach is less efficient in case of wideband signals since it introduces periodicity over the entire spectrum. A new alternative approach, which is part of the present invention, is disclosed whereby periodicity enhancement is achieved by filtering the innovative codevector \mathbf{c}_k from the innovative (fixed) codebook through an innovation filter 205 ($F(z)$) whose frequency response emphasizes the higher frequencies more than lower frequencies. The coefficients of $F(z)$ are related to the amount of periodicity in the excitation signal \mathbf{u} .

[0093] Many methods known to those skilled in the art are available for obtaining valid periodicity coefficients. For example, the value of gain b provides an indication of periodicity. That is, if gain b is close to 1, the periodicity of the excitation signal \mathbf{u} is high, and if gain b is less than 0.5, then periodicity is low.

[0094] Another efficient way to derive the filter $F(z)$ coefficients used in a preferred embodiment, is to relate them to the amount of pitch contribution in the total excitation signal \mathbf{u} . This results in a frequency response depending on the subframe periodicity, where higher frequencies are more strongly emphasized (stronger overall slope) for higher pitch gains. Innovation filter 205 has the effect of lowering the energy of the innovative codevector \mathbf{c}_k at low frequencies when the excitation signal \mathbf{u} is more periodic, which enhances the periodicity of the excitation signal \mathbf{u} at lower frequencies more than higher frequencies. Suggested forms for innovation filter 205 are

$$(1) \quad F(z)=1-\sigma z^{-1},$$

10

$$(2) \quad F(z)=-\alpha z+1-\alpha z^{-1}$$

15 or

where σ or α are periodicity factors derived from the level of periodicity of the excitation signal \mathbf{u} .

[0095] The second three-term form of $F(z)$ is used in a preferred embodiment. The periodicity factor α is computed in the voicing factor generator 204. Several methods can be used to derive the periodicity factor α based on the periodicity of the excitation signal \mathbf{u} . Two methods are presented below.

20 Method 1:

[0096] The ratio of pitch contribution to the total excitation signal \mathbf{u} is first computed in voicing factor generator 204 by

25

$$R_p = \frac{b^2 \mathbf{v}_T^t \mathbf{v}_T}{\mathbf{u}^t \mathbf{u}} = \frac{b^2 \sum_{n=0}^{N-1} \mathbf{v}_T^2(n)}{\sum_{n=0}^{N-1} \mathbf{u}^2(n)}$$

30

where \mathbf{v}_T is the pitch codebook vector, b is the pitch gain, and \mathbf{u} is the excitation signal \mathbf{u} given at the output of the adder 219 by

35

$$\mathbf{u} = g\mathbf{c}_k + b\mathbf{v}_T$$

[0097] Note that the term $b\mathbf{v}_T$ has its source in the pitch codebook (pitch codebook) 201 in response to the pitch lag T and the past value of \mathbf{u} stored in memory 203. The pitch codevector \mathbf{v}_T from the pitch codebook 201 is then processed through a low-pass filter 202 whose cut-off frequency is adjusted by means of the index j from the demultiplexer 217. The resulting codevector \mathbf{v}_T is then multiplied by the gain b from the demultiplexer 217 through an amplifier 226 to obtain the signal $b\mathbf{v}_T$.

[0098] The factor a is calculated in voicing factor generator 204 by

45

$$\alpha = qR_p$$

50

bounded by $\alpha < q$

where q is a factor which controls the amount of enhancement (q is set to 0.25 in this preferred embodiment).

Method 2:

[0099] Another method used in a preferred embodiment of the invention for calculating periodicity factor α is discussed below.

[0100] First, a voicing factor r_v is computed in voicing factor generator 204 by

$$r_v = (E_v - E_c) / (E_v + E_c)$$

5 where E_v is the energy of the scaled pitch codevector $b\mathbf{v}_T$ and E_c is the energy of the scaled innovative codevector $g\mathbf{c}_k$. That is

$$10 \quad E_v = b^2 \mathbf{v}_T^t \mathbf{v}_T = b^2 \sum_{n=0}^{N-1} v_T^2(n)$$

15 and

$$20 \quad E_c = g^2 \mathbf{c}_k^t \mathbf{c}_k = g^2 \sum_{n=0}^{N-1} c_k^2(n)$$

[0101] Note that the value of r_v lies between -1 and 1 (1 corresponds to purely voiced signals and -1 corresponds to purely unvoiced signals).

25 **[0102]** In this preferred embodiment, the factor α is then computed in voicing factor generator 204 by

$$\alpha = 0.125(1 + r_v)$$

30 which corresponds to a value of 0 for purely unvoiced signals and 0.25 for purely voiced signals.

[0103] In the first, two-term form of $F(z)$, the periodicity factor σ can be approximated by using $\sigma = 2\alpha$ in methods 1 and 2 above. In such a case, the periodicity factor σ is calculated as follows in method 1 above:

$$35 \quad \sigma = 2qR_p$$

bounded by $\sigma < 2q$.

[0104] In method 2, the periodicity factor σ is calculated as follows:

$$40 \quad \sigma = 0.25(1 + r_v).$$

[0105] The enhanced signal \mathbf{c}_f is therefore computed by filtering the scaled innovative codevector $g\mathbf{c}_k$ through the innovation filter 205 ($F(z)$).

45 **[0106]** The enhanced excitation signal \mathbf{u}' is computed by the adder 220 as:

$$\mathbf{u}' = \mathbf{c}_f + b\mathbf{v}_T$$

50 **[0107]** Note that this process is not performed at the encoder 100. Thus, it is essential to update the content of the pitch codebook 201 using the excitation signal \mathbf{u} without enhancement to keep synchronism between the encoder 100 and decoder 200. Therefore, the excitation signal \mathbf{u} is used to update the memory 203 of the pitch codebook 201 and the enhanced excitation signal \mathbf{u}' is used at the input of the LP synthesis filter 206.

55 **Synthesis and deemphasis**

[0108] The synthesized signal \mathbf{s}' is computed by filtering the enhanced excitation signal \mathbf{u}' through the LP synthesis filter 206 which has the form $1/\hat{A}(z)$, where $\hat{A}(z)$ is the interpolated LP filter in the current subframe. As can be seen in

Figure 2, the quantized LP coefficients $\hat{A}(z)$ on line 225 from demultiplexer 217 are supplied to the LP synthesis filter 206 to adjust the parameters of the LP synthesis filter 206 accordingly. The deemphasis filter 207 is the inverse of the preemphasis filter 103 of Figure 1. The transfer function of the deemphasis filter 207 is given by

5

$$D(z) = 1 / (1 - \mu z^{-1})$$

where μ is a preemphasis factor with a value located between 0 and 1 (a typical value is $\mu = 0.7$). A higher-order filter could also be used.

10 [0109] The vector s' is filtered through the deemphasis filter $D(z)$ (module 207) to obtain the vector s_d , which is passed through the high-pass filter 208 to remove the unwanted frequencies below 50 Hz and further obtain s_h .

Oversampling and high-frequency regeneration

15 [0110] The over-sampling module 209 conducts the inverse process of the down-sampling module 101 of Figure 1. In this preferred embodiment, oversampling converts from the 12.8 kHz sampling rate to the original 16 kHz sampling rate, using techniques well known to those of ordinary skill in the art. The oversampled synthesis signal is denoted \hat{s} . Signal \hat{s} is also referred to as the synthesized wideband intermediate signal.

20 [0111] The oversampled synthesis \hat{s} signal does not contain the higher frequency components which were lost by the downsampling process (module 101 of Figure 1) at the encoder 100. This gives a low-pass perception to the synthesized speech signal. To restore the full band of the original signal, a high frequency generation procedure is disclosed. This procedure is performed in modules 210 to 216, and adder 221, and requires input from voicing factor generator 204 (Figure 2).

25 [0112] In this new approach, the high frequency contents are generated by filling the upper part of the spectrum with a white noise properly scaled in the excitation domain, then converted to the speech domain, preferably by shaping it with the same LP synthesis filter used for synthesizing the down-sampled signal \hat{s} .

[0113] The high frequency generation procedure in accordance with the present invention is described hereinbelow.

30 [0114] The random noise generator 213 generates a white noise sequence w' with a flat spectrum over the entire frequency bandwidth, using techniques well known to those of ordinary skill in the art. The generated sequence is of length N which is the subframe length in the original domain. Note that N is the subframe length in the down-sampled domain. In this preferred embodiment, $N=64$ and $N'=80$ which correspond to 5 ms.

35 [0115] The white noise sequence is properly scaled in the gain adjusting module 214. Gain adjustment comprises the following steps. First, the energy of the generated noise sequence w' is set equal to the energy of the enhanced excitation signal u' computed by an energy computing module 210, and the resulting scaled noise sequence is given by

35

40

$$w(n) = w'(n) \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N'-1} w'^2(n)}} , \quad n=0, \dots, N'-1.$$

45

[0116] The second step in the gain scaling is to take into account the high frequency contents of the synthesized signal at the output of the voicing factor generator 204 so as to reduce the energy of the generated noise in case of voiced segments (where less energy is present at high frequencies compared to unvoiced segments). In this preferred embodiment, measuring the high frequency contents is implemented by measuring the tilt of the synthesis signal through a spectral tilt calculator 212 and reducing the energy accordingly. Other measurements such as zero crossing measurements can equally be used. When the tilt is very strong, which corresponds to voiced segments, the noise energy is further reduced. The tilt factor is computed in module 212 as the first correlation coefficient of the synthesis signal s_h and it is given by:

55

5

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

10

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$,
where voicing factor r_v is given by

15

$$r_v = (E_v - E_c) / (E_v + E_c)$$

20 where E_v is the energy of the scaled pitch codevector bv_T and E_c is the energy of the scaled innovative codevector gc_k , as described earlier. Voicing factor r_v is most often less than tilt but this condition was introduced as a precaution against high frequency tones where the tilt value is negative and the value of r_v is high. Therefore, this condition reduces the noise energy for such tonal signals.

[0117] The tilt value is 0 in case of flat spectrum and 1 in case of strongly voiced signals, and it is negative in case of unvoiced signals where more energy is present at high frequencies.

25 **[0118]** Different methods can be used to derive the scaling factor g_t from the amount of high frequency contents. In this invention, two methods are given based on the tilt of signal described above.

Method 1:

30 **[0119]** The scaling factor g_t is derived from the tilt by

$$g_t = 1 - \text{tilt}$$

bounded by $0.2 \leq g_t \leq 1.0$

35 For strongly voiced signal where the tilt approaches 1, g_t is 0.2 and for strongly unvoiced signals g_t becomes 1.0.

Method 2:

40 **[0120]** The tilt factor g_t is first restricted to be larger or equal to zero, then the scaling factor is derived from the tilt by

$$g_t = 10^{-0.6 \text{tilt}}$$

45 **[0121]** The scaled noise sequence w_g produced in gain adjusting module 214 is therefore given by:

$$w_g = g_t w.$$

50 **[0122]** When the tilt is close to zero, the scaling factor g_t is close to 1, which does not result in energy reduction. When the tilt value is 1, the scaling factor g_t results in a reduction of 12 dB in the energy of the generated noise.

[0123] Once the noise is properly scaled (w_g), it is brought into the speech domain using the spectral shaper 215. In the preferred embodiment, this is achieved by filtering the noise w_g through a bandwidth expanded version of the same LP synthesis filter used in the down-sampled domain ($1/\sqrt{0.8}$). The corresponding bandwidth expanded LP filter coefficients are calculated in spectral shaper 215.

55 **[0124]** The filtered scaled noise sequence w_g is then band-pass filtered to the required frequency range to be restored using the band-pass filter 216. In the preferred embodiment, the band-pass filter 216 restricts the noise sequence to the frequency range 5.6-7.2 kHz. The resulting band-pass filtered noise sequence z is added in adder 221 to the oversampled synthesized speech signal \hat{s} to obtain the final reconstructed sound signal s_{out} on the output 223.

[0125] Although the present invention has been described hereinabove by way of a preferred embodiment thereof, this embodiment can be modified at will, within the scope of the appended claims. Even though the preferred embodiment discusses the use of wideband speech signals, it will be obvious to those skilled in the art that the subject invention is also directed to other embodiments using wideband signals in general and that it is not necessarily limited to speech applications.

Claims

- 10 1. A device for recovering a high frequency content of a wideband signal previously down-sampled and for injecting said high frequency content in an over-sampled synthesized version of said wideband signal to produce a full-spectrum synthesized wideband signal, said high-frequency content recovering device comprising:
 - a) a random noise generator (213) for producing a noise sequence having a given spectrum;
 - b) a spectral shaping unit (215) for shaping the spectrum of the noise sequence in relation to linear prediction filter coefficients related to said down-sampled wideband signal; and
 - c) a signal injection circuit (221) for injecting said spectrally-shaped noise sequence in said over-sampled synthesized signal version to thereby produce said full-spectrum synthesized wideband signal (223).
- 20 2. A device as defined in claim 1, wherein said random noise generator is a random white noise generator for producing a white noise sequence having a flat spectrum over the entire frequency bandwidth of the wideband signal, whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.
- 25 3. A device as defined in claim 2, wherein said spectral shaping unit comprises:
 - a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
 - b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of said linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
 - c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.
- 35 4. A method for recovering a high frequency content of a wideband signal previously down-sampled and for injecting said high frequency content in an over-sampled synthesized version of said wideband signal to produce a full-spectrum synthesized wideband signal, said high-frequency content recovering method comprising:
 - a) randomly generating a noise sequence having a given spectrum;
 - b) spectrally-shaping said noise sequence in relation to linear prediction filter coefficients related to said down-sampled wideband signal; and
 - c) injecting said spectrally-shaped noise sequence in said over-sampled synthesized signal version to thereby produce said full-spectrum synthesized wideband signal.
- 45 5. A method as defined in claim 4, wherein generating said noise sequence comprises randomly generating a white noise sequence whereby said spectral shaping of the noise sequence produces a spectrally-shaped white noise sequence.
- 50 6. A method as defined in claim 5, wherein said spectral shaping of the noise sequence comprises:
 - a) producing a scaled white noise sequence in response to said white noise sequence and a set of gain adjusting parameters;
 - b) filtering said scaled white noise sequence in relation to a bandwidth expanded version of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
 - c) band-pass filtering said filtered scaled white noise sequence to produce a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-

shaped white noise sequence.

7. A decoder for producing a synthesized wideband signal, comprising:

- 5 a) a signal fragmenting device for receiving an encoded version of a wideband signal previously down-sampled during encoding and extracting from said encoded wideband signal version at least pitch codebook parameters, innovative codebook parameters, and linear prediction filter coefficients;
- 10 b) a pitch codebook responsive to said pitch codebook parameters for producing a pitch codevector;
- 15 c) an innovative codebook responsive to said innovative codebook parameters for producing an innovative codevector;
- 20 d) a combiner circuit for combining said pitch codevector and said innovative codevector to thereby produce an excitation signal;
- 25 e) a signal synthesis device including a linear prediction filter for filtering said excitation signal in relation to said linear prediction filter coefficients to thereby produce a synthesized wideband signal, and an oversampler responsive to said synthesized wideband signal for producing an over-sampled signal version of the synthesized wideband signal; and
- 30 f) a high-frequency content recovering device as recited in claim 1 for recovering a high frequency content of said wideband signal and for injecting said high frequency content in said over-sampled signal version to produce the full-spectrum synthesized wideband signal.

8. A decoder for producing a synthesized wideband signal as defined in claim 7, wherein said random noise generator comprises a random white noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

9. A decoder for producing a synthesized wideband signal as defined in claim B, wherein said spectral shaping unit comprises:

- 30 a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
- 35 b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
- 40 c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

10. A decoder for producing a synthesized wideband signal as defined in claim 9, further comprising:

- 40 a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
- 45 b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
- 50 c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

wherein said set of gain adjusting parameters comprises said voicing factor, said excitation energy, and said tilt scaling factor.

11. A decoder for producing a synthesized wideband signal as defined in claim 10, wherein said voicing factor generator comprises a means for calculating said voicing factor r_v using the relation:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

55

where E_v is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

12. A decoder for producing a synthesized wideband signal as defined in claim 10, wherein said gain adjusting unit comprises a means for calculating an energy scaling factor using the relation:

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

- 15 13. A decoder for producing a synthesized wideband signal as defined in claim 10, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 1 - \text{tilt}$$

20 bounded by $0.2 \leq g_t \leq 1.0$
where

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

25 conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

- 30 14. A decoder for producing a synthesized wideband signal as defined in claim 10, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 10^{-0.6\text{tilt}}$$

40 bounded by $0.2 \leq g_t \leq 1.0$
where

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

45 conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

- 50 55 15. A decoder for producing a synthesized wideband signal as defined in claim 9, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

16. A decoder for producing a synthesized wideband signal, comprising:

- a) a signal fragmenting device for receiving an encoded version of a wideband signal previously down-sampled during encoding and extracting from said encoded wideband signal version at least pitch codebook parameters, innovative codebook parameters, and linear prediction filter coefficients;
- b) a pitch codebook responsive to said pitch codebook parameters for producing a pitch codevector;
- c) an innovative codebook responsive to said innovative codebook parameters for producing an innovative codevector;
- d) a combiner circuit for combining said pitch codevector and said innovative codevector to thereby produce an excitation signal; and
- e) a signal synthesis device including a linear prediction filter for filtering said excitation signal in relation to said linear prediction filter coefficients to thereby produce a synthesized wideband signal, and an oversampler responsive to said synthesized wideband signal for producing an over-sampled signal version of the synthesized wideband signal;

the decoder comprising a high-frequency content recovering device as recited in claim 1 for recovering a high frequency content of said wideband signal and for injecting said high frequency content in said over-sampled signal version to produce the full-spectrum synthesized wideband signal.

17. A decoder for producing a synthesized wideband signal as defined in claim 16, wherein said random noise generator comprises a random white noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

18. A decoder for producing a synthesized wideband signal as defined in claim 17, wherein said spectral shaping unit comprises:

- a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
- b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of said linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
- c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

19. A decoder for producing a synthesized wideband signal as defined in claim 18, further comprising:

- a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
- b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
- c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

wherein said set of gain adjusting parameters comprises said voicing factor, said energy scaling factor, and said tilt scaling factor.

20. A decoder for producing a synthesized wideband signal as defined in claim 19, wherein said voicing factor generator comprises a means for calculating said voicing factor r_v using the relation:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

where E_v is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

21. A decoder for producing a synthesized wideband signal as defined in claim 19, wherein said gain adjusting unit

comprises a means for calculating an energy scaling factor using the relation:

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} \quad n=0, \dots, N-1.$$

where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

- 22.** A decoder for producing a synthesized wideband signal as defined in claim 19, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 1 - \text{tilt}$$

bounded by $0.2 \leq g_t \leq 1.0$

where

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

- 23.** A decoder for producing a synthesized wideband signal as defined in claim 19, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 10^{-0.6\text{tilt}}$$

bounded by $0.2 \leq g_t \leq 1.0$

where

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

- 24.** A decoder for producing a synthesized wideband signal as defined in claim 18, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

25. A cellular communication system for servicing a large geographical area divided into a plurality of cells, comprising:

- a) mobile transmitter/receiver units;
- b) cellular base stations respectively situated in said cells;
- c) a control terminal for controlling communication between the cellular base stations;
- d) a bidirectional wireless communication sub-system between each mobile unit situated in one cell and the cellular base station of said one cell, said bidirectional wireless communication subsystem comprising, in both the mobile unit and the cellular base station:
 - i) a transmitter including an encoder for encoding a wideband signal and a transmission circuit for transmitting the encoded wideband signal; and
 - ii) a receiver including a receiving circuit for receiving a transmitted encoded wideband signal and a decoder as recited in claim 7 for decoding the received encoded wideband signal.

10 26. A cellular communication system as defined in claim 26, wherein said random noise generator comprises a random white noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

15 27. A cellular communication system as defined in claim 26, wherein said spectral shaping unit comprises:

- a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
- b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
- c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

20 28. A cellular communication system as defined in claim 27, further comprising:

- a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
- b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
- c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

25 40 wherein said set of gain adjusting parameters comprises said voicing factor, said excitation energy, and said tilt scaling factor.

29. A cellular communication system as defined in claim 28, wherein said voicing factor generator comprises a means 45 for calculating said voicing factor r_V using the relation:

$$r_V = (E_V - E_c) / (E_V + E_c)$$

50 where E_V is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

30. A cellular communication system as defined in claim 28, wherein said gain adjusting unit comprises a means for calculating an energy scaling factor using the relation:

5

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , \quad n=0, \dots, N-1.$$

10

where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

- 15 31. A cellular communication system as defined in claim 28, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 1 - \text{tilt}$$

20

bounded by $0.2 \leq g_t \leq 1.0$
where

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

30

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

35

32. A cellular communication system as defined in claim 28, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

40

$$g_t = 10^{-0.6\text{tilt}}$$

bounded by $0.2 \leq g_t \leq 1.0$
where

45

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

50

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

55

33. A cellular communication system as defined in claim 27, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

34. A cellular mobile transmitter/receiver unit comprising:

- a) a transmitter including an encoder for encoding a wideband signal and a transmission circuit for transmitting the encoded wideband signal; and
- b) a receiver including a receiving circuit for receiving a transmitted encoded wideband signal and a decoder as recited in claim 7 for decoding the received encoded wideband signal.

35. A cellular mobile transmitter/receiver unit as defined in claim 34, wherein said random noise generator comprises a random white noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

36. A cellular mobile transmitter/receiver unit as defined in claim 35, wherein said spectral shaping unit comprises:

- a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
- b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
- c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

37. A cellular mobile transmitter/receiver unit as defined in claim 36, further comprising:

- a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
- b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
- c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

wherein said set of gain adjusting parameters comprises said voicing factor, said excitation energy, and said tilt scaling factor.

38. A cellular mobile transmitter/receiver unit as defined in claim 37, wherein said voicing factor generator comprises a means for calculating said voicing factor r_v using the relation:

$$r_v = (E_v - E_c)/(E_v + E_c)$$

where E_v is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

39. A cellular mobile transmitter/receiver unit as defined in claim 37, wherein said gain adjusting unit comprises a means for calculating an energy scaling factor using the relation:

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} ; \quad n=0, \dots, N-1.$$

where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

EP 1 125 284 B1

40. A cellular mobile transmitter/receiver unit as defined in claim 37, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

$$g_t = 1 - \text{tilt}$$

5

bounded by $0.2 \leq g_t \leq 1.0$
where

10

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

15

20

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

41. A cellular mobile transmitter/receiver unit as defined in claim 37, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

25

$$g_t = 10^{-0.6\text{tilt}}$$

30

bounded by $0.2 \leq g_t \leq 1.0$
where

35

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

40

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

42. A cellular mobile transmitter/receiver unit as defined in claim 36, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

45

43. A cellular network element comprising:

50

- a) a transmitter including an encoder for encoding a wideband signal and a transmission circuit for transmitting the encoded wideband signal; and
- b) a receiver including a receiving circuit for receiving a transmitted encoded wideband signal and a decoder as recited in claim 7 for decoding the received encoded wideband signal.

55

44. A cellular network element as defined in claim 43, wherein said random noise generator comprises a random white noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

45. A cellular network element as defined in claim 44, wherein said spectral shaping unit comprises:

- 5 a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
 b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and
 c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

10 **46.** A cellular network element as defined in claim 45, further comprising:

- 15 a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
 b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
 c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

20 wherein said set of gains adjusting parameters comprises said voicing factor, said excitation energy, and said tilt scaling factor.

25 **47.** A cellular network element as defined in claim 46, wherein said voicing factor generator comprises a means for calculating said voicing factor r_v using the relation:

$$r_v = (E_v - E_c)/(E_v + E_c)$$

30 where E_v is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

35 **48.** A cellular network element as defined in claim 46, wherein said gain adjusting unit comprises a means for calculating an energy scaling factor using the relation:

40
$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

45 where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

49. A cellular network element as defined in claim 46, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

50
$$g_t = 1 - \text{tilt}$$

55 bounded by $0.2 \leq g_t \leq 1.0$

 where

5

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

10

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

50. A cellular network element as defined in claim 46, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

15

$$g_t = 10^{-0.6\text{tilt}}$$

20

bounded by $0.2 \leq g_t \leq 1.0$

where

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

30

conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

51. A cellular network element as defined in claim 45, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

35

52. A cellular communication system for servicing a large geographical area divided into a plurality of cells, comprising: mobile transmitter/receiver units; cellular base stations, respectively situated in said cells; and control terminal for controlling communication between the cellular base stations:

40

a bidirectional wireless communication sub-system between each mobile unit situated in one cell and the cellular base station of said one cell, said bidirectional wireless communication sub-system comprising, in both the mobile unit and the cellular base station:

45

- a) a transmitter including an encoder for encoding a wideband signal and a transmission circuit for transmitting the encoded wideband signal; and
- b) a receiver including a receiving circuit for receiving a transmitted encoded wideband signal and a decoder as recited in claim 7 for decoding the received encoded wideband signal.

50

53. A bidirectional wireless communication sub-system as defined in claim 52, wherein said random noise generator comprises a random write noise generator for producing a white noise sequence whereby said spectral shaping unit produces a spectrally-shaped white noise sequence.

55

54. A bidirectional wireless communication sub-system as defined in claim 53, wherein said spectral shaping unit comprises:

- a) a gain adjustment module, responsive to said white noise sequence and a set of gain adjusting parameters, for producing a scaled white noise sequence;
- b) a spectral shaper for filtering said scaled white noise sequence in relation to a bandwidth expanded version

of the linear prediction filter coefficients to produce a filtered scaled white noise sequence comprising a frequency bandwidth generally higher than a frequency bandwidth of said over-sampled synthesized signal version; and

5 c) a band-pass filter responsive to said filtered scaled white noise sequence for producing a band-pass filtered scaled white noise sequence to be subsequently injected in said over-sampled synthesized signal version as said spectrally-shaped white noise sequence.

55. A bidirectional wireless communication sub-system as defined in claim 54, further comprising:

- 10 a) a voicing factor generator responsive to said adaptive and innovative codevectors for calculating a voicing factor for forwarding to said gain adjustment module;
- b) an energy computing module responsive to said excitation signal for calculating an excitation energy for forwarding to said gain adjustment module; and
- 15 c) a spectral tilt calculator responsive to said synthesized signal for calculating a tilt scaling factor for forwarding to said gain adjustment module;

wherein said set of gain adjusting parameters comprises said voicing factor, said excitation energy, and said tilt scaling factor.

20 **56.** A bidirectional wireless communication sub-system as defined in claim 55, wherein said voicing factor generator comprises a means for calculating said voicing factor r_v using the relation:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

25 where E_v is the energy of a gain-scaled version of the pitch codevector and E_c is the energy of a gain-scaled version of the innovative codevector.

30 **57.** A bidirectional wireless communication sub-system as defined in claim 55, wherein said gain adjusting unit comprises a means for calculating an energy scaling factor using the relation:

35 *Energy scaling factor* = $\sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , \quad n=0, \dots, N-1.$

40 where w' is said white noise sequence and u' is an enhanced excitation signal derived from said excitation signal.

58. A bidirectional wireless communication sub-system as defined in claim 55, wherein said spectral tilt calculator comprises a means for calculating said tilt scaling factor g_t using the relation:

45
$$g_t = 1 - \text{tilt}$$

50 bounded by $0.2 \leq g_t \leq 1.0$

where

5

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

10 conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

59. A bidirectional wireless communication sub-system as defined in claim 55, wherein said spectral tilt calculator comprising a means for calculating said tilt scaling factor g_t using the relation:

15

$$g_t = 10^{-0.6\text{tilt}}$$

bounded by $0.2 \leq g_t \leq 1.0$

where

20

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)},$$

30 conditioned by $\text{tilt} \geq 0$ and $\text{tilt} \geq r_v$

60. A bidirectional wireless communication sub-system as defined in claim 54, wherein said band-pass filter comprises a frequency bandwidth located between 5.6 kHz and 7.2 kHz.

35

Patentansprüche

1. Vorrichtung zur Wiederherstellung eines Hochfrequenzanteils eines vorher abwärts abgetasteten Breitbandsignals und zur Einspeisung des Hochfrequenzanteils in eine überabgetastete synthetisierte Version des Breitbandsignals, um ein synthetisiertes Breitbandsignal mit vollem Spektrum zu erzeugen, wobei die Vorrichtung zur Wiederherstellung des Hochfrequenzanteils umfaßt:
 - a) einen Rauschzufallsgenerator (213) zur Erzeugung einer Rauschsequenz mit einem gegebenen Spektrum;
 - b) eine spektrale Formeinheit (215) zur Formung des Spektrums der Rauschsequenz in bezug auf lineare Prädiktionsfilterkoeffizienten, die mit dem abwärts abgetasteten Breitbandsignal verknüpft sind;
 - c) einen Signaleinspeisekreis (221) zur Einspeisung der spektralgeformten Rauschsequenz in die überabgetastete, synthetisierte Signalversion, um hierdurch das synthetisierte Breitbandsignal mit vollem Spektrum (223) zu erzeugen.
2. Vorrichtung nach Anspruch 1, bei der der Rauschzufallsgenerator ein Zufallsgenerator für weißes Rauschen ist, um eine Sequenz weißen Rauschens zu erzeugen, die über die gesamte Frequenzbandbreite des Breitbandsignals ein flaches Spektrum aufweist, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.
3. Vorrichtung nach Anspruch 2, bei der die spektrale Formeinheit umfaßt:
 - a) ein Verstärkungseinstellmodul, das auf die Sequenz weißen Rauschens ansprechend ist, und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;

- 5 b) einen Spektralformer zur Filterung der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite erweiterte Version der linearen Prädiktionsfilterkoeffizienten, um eine gefilterte, skalierte Sequenz weißen Rauschens zu erzeugen, umfassend eine Frequenzbandbreite, die allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion ist; und
c) ein Bandpaßfilter, das ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens ist, um eine bandpaßgefilterte, skalierte Sequenz weißen Rauschens für eine anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens zu erzeugen.

- 10 4. Verfahren zur Wiederherstellung eines Hochfrequenzanteils eines vorher abwärts abgetasteten Breitbandsignals und zur Einspeisung des Hochfrequenzanteils in eine überabgetastete, synthetisierte Version des Breitbandsignals, um ein synthetisiertes Breitbandsignal mit vollem Spektrum zu erzeugen, wobei das Verfahren zur Wiederherstellung des Hochfrequenzanteils umfaßt:

- 15 a) die zufällige Erzeugung einer Rauschsequenz mit einem gegebenen Spektrum;
b) eine Spektralformung der Rauschsequenz in bezug auf lineare Prädiktionsfilterkoeffizienten, die mit dem abwärts abgetasteten Breitbandsignal verknüpft sind; und
c) Einspeisung der spektralgeformten Rauschsequenz in die überabgetastete, synthetisierte Signalversion, um hierdurch das synthetisierte Breitbandsignal mit vollem Spektrum zu erzeugen.

- 20 5. Verfahren nach Anspruch 4, bei dem die Erzeugung der Rauschsequenz umfaßt, das zufällig eine Sequenz weißen Rauschens erzeugt wird, wodurch die spektrale Formung der Rauschsequenz eine spektralgeformte Sequenz weißen Rauschens erzeugt.

- 25 6. Verfahren nach Anspruch 5, bei dem die spektrale Formung der Rauschsequenz umfaßt:

- 25 a) Erzeugung einer skalierten Sequenz weißen Rauschens ansprechend auf die Sequenz weißen Rauschens und eines Satzes von Verstärkungseinstellparametern;
b) Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten, um eine gefilterte, skalierte Sequenz weißen Rauschens zu erzeugen, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion; und
c) Bandpaßfiltern der gefilterten, skalierten Sequenz weißen Rauschens, um eine bandpaßgefilterte, skalierte Sequenz weißen Rauschens für eine anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens zu erzeugen.

- 35 7. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals, umfassend:

- 40 a) eine Signalfragmentierungsvorrichtung zur Aufnahme einer codierten Version eines vorher während der Codierung abwärts abgetasteten Breitbandsignals und Extrahierung wenigstens von Tonhöhen-Codebuchparametern, innovativen Codebuchparametern und linearen Prädiktionsfilterkoeffizienten aus der codierten Breitbandsignalversion;
b) ein Tonhöhen-Codebuch ansprechend auf die Tonhöhen-Codebuchparameter zur Erzeugung eines Tonhöhen-Codevektors;
c) ein innovatives Codebuch ansprechend auf die innovativen Codebuchparameter zur Erzeugung eines innovativen Codevektors;
d) einen Kombinatorikreis zum Kombinieren des Tonhöhen-Codevektors und des innovativen Codevektors, um hierdurch ein Erregungssignal zu erzeugen;
e) eine Signalsynthesevorrichtung, die ein lineares Prädiktionsfilter zum Filtern des Erregungssignals in bezug auf die linearen Prädiktionsfilterkoeffizienten enthält, um hierdurch ein synthetisiertes Breitbandsignal zu erzeugen, und eine auf das synthetisierte Breitbandsignal ansprechende Überabtasteinrichtung zur Erzeugung einer überabgetasteten Signalversion des synthetisierten Breitbandsignals; und
50 f) eine Vorrichtung zur Wiederherstellung des Hochfrequenzanteils, wie aufgeführt in Anspruch 1, zur Wiederherstellung eines Hochfrequenzanteils des Breitbandsignals und zur Einspeisung des Hochfrequenzanteils in die überabgetastete Signalversion zur Erzeugung des synthetisierten Breitbandsignals mit vollem Spektrum.

- 55 8. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 7, bei dem der Rauschzufallsgenerator einen Zufallsgenerator für weißes Rauschen zur Erzeugung einer Sequenz weißen Rauschens umfaßt, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

EP 1 125 284 B1

9. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 8, bei dem die spektrale Formeinheit umfaßt:

- 5 a) ein Verstärkungseinstellmodul ansprechend auf die Sequenz weißen Rauschens und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;
- 10 b) einen Spektralformer zur Filterung der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten, um eine gefilterte, skalierte Sequenz weißen Rauschens zu erzeugen, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion; und
- 15 c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer bandpaßgefilterten, skalierten Sequenz weißen Rauschens für die anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektral geformte Sequenz weißen Rauschens.

10. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 9, weiter umfassend:

- 15 a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevectoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;
- 20 b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul;
- 25 c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenskalierungsfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

wobei der Satz der Verstärkungseinstellparameter den Stimmfaktor, die Erregungsenergie und den Dachschrägenkalierungsfaktor umfaßt.

11. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 10, bei dem der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

wobei E_v die Energie einer verstärkungskalierten Version des Tonhöhen-Codevectors ist und E_c die Energie einer verstärkungskalierten Version des innovativen Codevectors ist.

12. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 10, bei dem die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Relation umfaßt:

$$40 \quad \text{Energieskalierungsfaktor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} \quad , \quad n=0, \dots, N-1.$$

wobei w' die Sequenz weißen Rauschens ist und u' ein von dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

13. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 10, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter der Verwendung der Relation umfaßt:

$$55 \quad g_t = 1 - tilt$$

begrenzt durch $0,2 \leq g_t \leq 1,0$

wobei

5

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10

bedingt durch $tilt \geq 0$ und $tilt \geq r_V$.

15

- 14.** Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 10, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenkalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$g_t = 10^{-0.6 \cdot tilt}$$

20

begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

25

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

30

bedingt durch $tilt \geq 0$ und $tilt \geq r_V$.

35

- 15.** Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 9, bei dem das Tiefpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

40

- 16.** Decodierer zur Erzeugung eines synthetisierten Breitbandsignals, umfassend:

a) eine Signalfragmentierungsvorrichtung zur Aufnahme einer codierten Version eines Breitbandsignals, das vorher während der Codierung und der Extrahierung wenigstens von Dachschrägen-Codebuchparametern, innovativen Codebuchparametern und linearen Prädiktionsfilterkoeffizienten aus der codierten Breitbandsignalversion abgetastet wurde;

b) ein Dachschrägen-Codebuch ansprechend auf die Dachschrägen-Codebuchparameter zur Erzeugung eines Dachschrägen-Codevectors;

c) ein innovatives Codebuch ansprechend auf die innovativen Codebuchparameter zur Erzeugung eines innovativen Codevectors;

d) einen Kombinatorkreis zur Kombination des Dachschrägen-Codevektors und des innovativen Codevektors, um hierdurch ein Erregungssignal zu erzeugen; und

e) eine Signalsynthesevorrichtung, die ein lineares Prädiktionsfilter zum Filtern des Erregungssignals in bezug auf die linearen Prädiktionsfilterkoeffizienten, um hierdurch ein synthetisiertes Breitbandsignal zu erzeugen, und eine Überabtasteinrichtung ansprechend auf das synthetisierte Breitbandsignal zur Erzeugung einer über-abgetasteten Signalversion des synthetisierten Breitbandsignals enthält;

50

wobei der Decodierer eine Vorrichtung zur Wiederherstellung des Hochfrequenzanteils, wie aufgeführt in Anspruch 1, umfaßt, um einen Hochfrequenzanteil des Breitbandsignals wiederherzustellen und um den Hochfrequenzanteil in die überabgetastete Signalversion einzuspeisen, um das synthetisierte Breitbandsignal mit vollem Spektrum zu erzeugen.

EP 1 125 284 B1

17. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 16, bei dem der Rauschzufallsgenerator einen Zufallsgenerator für weißes Rauschen umfaßt, um eine Sequenz weißen Rauschens zu erzeugen, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

5 18. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 17, bei dem die spektrale Formeinheit umfaßt:

a) ein Verstärkungseinstellmodul ansprechend auf die Sequenz weißen Rauschens und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;

10 b) einen Spektralformer zum Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten zur Erzeugung einer gefilterten, skalierten Sequenz weißen Rauschens, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion; und

15 c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer bandpaßgefilterten, skalierten Sequenz weißen Rauschens für die anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens.

19. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 18, weiter umfassend:

20 a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevektoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul; und

25 c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenskalierungsfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

wobei der Satz der Verstärkungseinstellparametern den Stimmfaktor, den Energieskalierungsfaktor und den Dachschrägenskalierungsfaktor umfaßt.

30 20. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 19, bei dem der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

35

wobei E_v die Energie einer verstärkungskalierten Version des Tonhöhen-Codevektors ist und E_c die Energie einer verstärkungskalierten Version des innovativen Codevektors ist.

40 21. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 19, bei dem die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Relation umfaßt:

$$\text{Energieskalierungsfaktor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

50

wobei w' die Sequenz weißen Rauschens ist und u' ein von dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

55 22. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 19, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$g_t = 1 - tilt$$

5 begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

10

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

15 bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

20 23. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 19, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$g_t = 10^{-0,6tilt}$$

25 begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

30

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

35 begrenzt durch $tilt \geq 0$ und $tilt \geq r_v$.

40 24. Decodierer zur Erzeugung eines synthetisierten Breitbandsignals nach Anspruch 18, bei dem das Bandpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

25. Zellulares Kommunikationssystem zur Versorgung eines großen geographischen Bereichs, der in eine Vielzahl von Zellen unterteilt ist, umfassend:

45 a) mobile Sender/Empfängereinheiten;
b) zellulare Basisstationen, die sich jeweils in den Zellen befinden;
c) eine Leitstation zur Steuerung der Kommunikation zwischen den zellularen Basisstationen;
d) ein bidirektionales, drahtloses Kommunikationsteilsystem zwischen jeder in einer Zelle befindlichen mobilen Einheit und der zellularen Basisstation der einen Zelle, wobei das bidirektionale, drahtlose Kommunikations-

50 teilsystem in der mobilen Einheit und auch in der zellularen Basisstation umfaßt:

55 i) einen Sender, der einen Codierer zur Codierung eines Breitbandsignals und einen Sendekreis zum Senden des codierten Breitbandsignals enthält; und
ii) einen Empfänger, der einen Empfängerkreis zum Empfangen eines gesendeten, codierten Breitbandsignals und einen Decodierer, wie in Anspruch 7 aufgeführt, zum Decodieren des empfangenen, codierten Breitbandsignals enthält.

26. Zellulares Kommunikationssystem nach Anspruch 25, bei dem der Rauschzufallsgenerator einen Zufallsgenerator

EP 1 125 284 B1

für weißes Rauschen umfaßt, um eine Sequenz weißen Rauschens zu erzeugen, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

27. Zellulares Kommunikationssystem nach Anspruch 26, bei dem die spektrale Formeinheit umfaßt:

- 5 a) ein Verstärkungseinstellmodul ansprechend auf die Sequenz weißen Rauschens und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;
- 10 b) einen Spektraformer zum Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten zur Erzeugung einer gefilterten, skalierten Sequenz weißen Rauschens, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion; und
- 15 c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer bandpaßgefilterten, skalierten Sequenz weißen Rauschens für die anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens.

28. Zellulares Kommunikationssystem nach Anspruch 27, weiter umfassend:

- 20 a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevektoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;
 - 25 b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul; und
 - 30 c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenkalierungsfaktors für die Übertragung an das Verstärkungseinstellmodul;
- wobei der Satz der Verstärkungseinstellparameter den Stimmfaktor, die Erregungsenergie und den Dachschrägenkalierungsfaktor umfaßt.

29. Zellulares Kommunikationssystem nach Anspruch 28, bei dem der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

wobei E_v die Energie einer verstärkungskalierten Version des Tonhöhen-Codevectors ist und E_c die Energie einer verstärkungsskalierten Version des innovativen Codevektors ist.

30. Zellulares Kommunikationssystem nach Anspruch 28, bei dem die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Relation umfaßt:

$$\text{Energieskalierungsfaktor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

wobei w' die Sequenz weißen Rauschens ist und u' ein aus dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

31. Zellulares Kommunikationssystem nach Anspruch 28, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenkalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$g_t = 1 - \text{tilt}$$

begrenzt durch $0,2 \leq g_t \leq 1,0$

wobei.

$$5 \quad \text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10

bedingt durch $\text{tilt} \geq 0$ und $\text{tilt} \geq r_v$.

- 15 32. Zellulares Kommunikationssystem nach Anspruch 28, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$20 \quad g_t = 10^{-0.6 \text{tilt}}$$

begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

30

bedingt durch $\text{tilt} \geq 0$ und $\text{tilt} \geq r_v$.

- 35 33. Zellulares Kommunikationssystem nach Anspruch 27, bei dem das Bandpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

34. Zellulare mobile Sender/Empfängereinheit umfassend:

- 40 a) einen Sender, der einen Codierer zur Codierung eines Breitbandsignals und einen Sendekreis zum Senden des codierten Breitbandsignals enthält; und
b) einen Empfänger, der einen Empfängererkreis zum Empfangen eines gesendeten, codierten Breitbandsignals und einen Decodierer, wie in nach Anspruch 7 aufgeführt, zum Decodieren des empfangenen, codierten Breitbandsignals enthält.

45

35. Zellulare mobile Sender/Empfängereinheit nach Anspruch 34, bei der der Rauschzufallsgenerator einen Zufallsgenerator für weißes Rauschen umfaßt, um eine Sequenz weißen Rauschens zu erzeugen, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

- 50 36. Zellulare mobile Sender/Empfängereinheit nach Anspruch 35, wobei die spektrale Formeinheit umfaßt:

- a) ein Verstärkungeinstellmodul, das auf die Sequenz weißen Rauschens ansprechend ist, und einen Satz von Verstärkungeinstellparametern, um eine skalierte Sequenz weißen Rauschens zu erzeugen;
b) einen Spektralformer zum Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten, um eine gefilterte, skalierte Sequenz weißen Rauschens zu erzeugen, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten, synthetisierten Signalversion; und
c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer

EP 1 125 284 B1

bandpaßgefilterten, skalierten Sequenz weißen Rauschens für die anschließenden Einspeisung in die über-abgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens.

- 37.** Zellulare mobile Sender/Empfängereinheit nach Anspruch 36, weiter umfassend:

- 5 a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevektoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;
 b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul; und
 10 c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenskalierungsfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

wobei der Satz der Verstärkungseinstellparameter den Stimmfaktor, die Erregungsenergie und den Dachschrägenkalierungsfaktor umfaßt.

- 15 **38.** Zellulare mobile Sender/Empfängereinheit nach Anspruch 37, bei der der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

20
$$r_v = (E_v - E_c) / (E_v + E_c)$$

wobei E_v die Energie einer verstärkungskalierten Version des Tonhöhen-Codevektors ist und E_c die Energie einer verstärkungskalierten Version des innovativen Codevektors ist.

- 25 **39.** Zellulare mobile Sender/Empfängereinheit nach Anspruch 37, bei der die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Relation umfaßt:

30 Energieskalierungsfaktor =
$$\sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} \quad , \quad n=0, \dots, N-1.$$

40 wobei w' die Sequenz weißen Rauschens ist und u' ein aus dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

- 45 **40.** Zellulare mobile Sender/Empfängereinheit nach Anspruch 37, bei der der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

50
$$g_t = 1 - tilt$$

begrenzt durch $0,2 \leq g_t \leq 1,0$

wobei

55
$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

41. Zellulare mobile Sender/Empfängereinheit nach Anspruch 37, bei der der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

5

$$g_t = 10^{-0.6tilt}$$

begrenzt durch $0,2 \leq g_t \leq 1,0$

10

wobei

15

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

20

bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

42. Zellulare mobile Sender/Empfängereinheit nach Anspruch 36, bei der das Bandpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

25

43. Zellulares Netzwerkelement, umfassend:

30

- a) einen Sender, der einen Codierer zur Codierung eines Breitbandsignals und einen Sendekreis zum Senden des codierten Breitbandsignals enthält; und
- b) einen Empfänger, der einen Empfängererkreis zum Empfangen eines gesendeten codierten Breitbandsignals und einen Decodierer, wie in Anspruch 7 aufgeführt, zum Decodieren des empfangenen, codierten Breitbandsignals enthält.

35

44. Zellulares Netzwerkelement nach Anspruch 43, bei dem der Rauschzufallsgenerator einen Zufallsgenerator für weißes Rauschen umfaßt, um eine Sequenz weißen Rauschens zu erzeugen, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

45. Zellulares Netzwerkelement nach Anspruch 44, bei dem die spektrale Formeinheit umfaßt:

40

- a) ein Verstärkungseinstellmodul, das auf die Sequenz weißen Rauschens ansprechend ist, und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;
- b) einen Spektralformer zum Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten zur Erzeugung einer gefilterten, skalierten Sequenz weißen Rauschens, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten synthetisierten Signalversion; und
- c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer bandpaßgefilterten, skalierten Sequenz weißen Rauschens für die anschließende Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens.

50

46. Zellulares Netzwerkelement nach Anspruch 45, weiter umfassend:

55

- a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevektoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;
- b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul; und
- c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenskalierungsfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

EP 1 125 284 B1

wobei der Satz der Verstärkungseinstellparameter den Stimmfaktor, die Erregungsenergie und den Dachschrägenkalierungsfaktor umfaßt.

47. Zellulares Netzwerkelement nach Anspruch 46, bei dem der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

10 wobei E_v die Energie einer verstärkungsskalierten Version des innovativen Codevectors ist.

48. Zellulares Netzwerkelement nach Anspruch 46, bei dem die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Relation umfaßt:

15

$$\text{Energieskalierungsfaktor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

20 wobei w' die Sequenz weißen Rauschens ist und u' ein aus dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

- 25 49. Zellulares Netzwerkelement nach Anspruch 46, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

30

$$g_t = 1 - tilt$$

begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

35

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

45

bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

- 50 50. Zellulares Netzwerkelement nach Anspruch 46, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

$$g_t = 10^{-0.6tilt}$$

55 begrenzt durch $0,2 \leq g_t \leq 1,0$
wobei

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

5

bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

10

51. Zellulares Netzwerkelement nach Anspruch 45, bei dem das Bandpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

15

52. Zellulares Kommunikationssystem zur Versorgung eines großen geographischen Bereichs, der in eine Vielzahl von Zellen unterteilt ist, umfassend: mobile Sender/Empfängereinheiten; zellulare Basisstationen, die sich jeweils in den Zellen befinden; und eine Leitstation zu Steuern der Kommunikation zwischen den zellularen Basisstationen:

20

ein bidirektionales, drahtloses Kommunikationsteilsystem zwischen jeder in einer Zelle befindlichen mobilen Einheit und der zellularen Basisstation der besagten einen Zelle, wobei das bidirektionale, drahtlose Kommunikationsteilsystem in der mobilen Einheit und auch in der zellularen Basisstation umfaßt:

25

- a) einen Sender, der einen Codierer zur Codierung eines Breitbandsignals und einen Sendekreis zum Senden des codierten Breitbandsignals enthält; und
- b) einen Empfänger, der einen Empfängerkreis zum Empfangen eines gesendeten, codierten Breitbandsignals und einen Decodierer, wie in Anspruch 7 aufgeführt, zum Decodieren des empfangenen, codierten Breitbandsignals enthält.

30

53. Bidirektionales drahtloses Kommunikationsteilsystem nach Anspruch 52, bei dem der Rauschzufallsgenerator einen Zufallsgenerator für weißes Rauschen zur Erzeugung einer Sequenz weißen Rauschens umfaßt, wodurch die spektrale Formeinheit eine spektralgeformte Sequenz weißen Rauschens erzeugt.

35

54. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 53, bei dem die spektrale Formeinheit umfaßt:

40

- a) ein Verstärkungseinstellmodul, das auf die Sequenz weißen Rauschens ansprechend ist, und einen Satz von Verstärkungseinstellparametern zur Erzeugung einer skalierten Sequenz weißen Rauschens;
- b) einen Spektralformer zum Filtern der skalierten Sequenz weißen Rauschens in bezug auf eine in der Bandbreite aufgeweitete Version der linearen Prädiktionsfilterkoeffizienten zur Erzeugung einer gefilterten, skalierten Sequenz weißen Rauschens, umfassend eine Frequenzbandbreite allgemein höher als eine Frequenzbandbreite der überabgetasteten synthetisierten Signalversion; und
- c) ein Bandpaßfilter ansprechend auf die gefilterte, skalierte Sequenz weißen Rauschens zur Erzeugung einer bandpaßgefilterten, skalierten Sequenz weißen Rauschens zur anschließenden Einspeisung in die überabgetastete, synthetisierte Signalversion als spektralgeformte Sequenz weißen Rauschens.

45

55. Bidirektionales drahtloses Kommunikationsteilsystem nach Anspruch 54, weiter umfassend:

50

- a) einen Stimmfaktorgenerator ansprechend auf die adaptiven und innovativen Codevektoren zur Berechnung eines Stimmfaktors für die Übertragung zu dem Verstärkungseinstellmodul;
- b) ein Energieberechnungsmodul ansprechend auf das Erregungssignal zur Berechnung einer Erregungsenergie für die Übertragung zu dem Verstärkungseinstellmodul; und
- c) einen spektralen Dachschrägenrechner ansprechend auf das synthetisierte Signal zur Berechnung eines Dachschrägenkalierungsfaktors für die Übertragung zu dem Verstärkungseinstellmodul;

55

wobei der Satz der Verstärkungseinstellparameter den Stimmfaktor, die Erregungsenergie und den Dachschrägenkalierungsfaktor umfaßt.

56. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 55, bei dem der Stimmfaktorgenerator ein Mittel zur Berechnung des Stimmfaktors r_v unter Verwendung der Relation umfaßt:

$$r_v = (E_v - E_c) / (E_v + E_c)$$

5 wobei E_v die Energie einer verstärkungskalierten Version des Dachschrägen-Codevektors ist und E_c die Energie einer verstärkungskalierten Version des innovativen Codevektors ist.

57. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 55, bei dem die Verstärkungseinstelleinheit ein Mittel zur Berechnung eines Energieskalierungsfaktors unter Verwendung der Gleichung umfaßt:

10

$$\text{Energieskalierungsfaktor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n=0, \dots, N-1.$$

15

20 wobei w' die Sequenz weißen Rauschens ist und u' ein aus dem Erregungssignal abgeleitetes verstärktes Erregungssignal ist.

- 25 58. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 55, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

30

$$g_t = 1 - tilt$$

35 begrenzt durch $0,2 \leq g_t \leq 1,0$

wobei

30

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

40

bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

45

59. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 55, bei dem der spektrale Dachschrägenrechner ein Mittel zur Berechnung des Dachschrägenskalierungsfaktors g_t unter Verwendung der Relation umfaßt:

45

$$g_t = 10^{-0,6tilt}$$

50

begrenzt durch $0,2 \leq g_t \leq 1,0$

wobei

55

5

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n) s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10 bedingt durch $tilt \geq 0$ und $tilt \geq r_v$.

60. Bidirektionales, drahtloses Kommunikationsteilsystem nach Anspruch 54, bei dem das Bandpaßfilter eine Frequenzbandbreite umfaßt, die zwischen 5,6 kHz und 7,2 kHz liegt.

15

Revendications

1. Un dispositif pour récupérer un contenu haute-fréquence d'un signal large-bande préalablement sous-échantilloné et pour injecter ledit contenu haute-fréquence dans une version synthétisée suréchantillonnée dudit signal large-bande afin de produire un signal large-bande synthétisé plein spectre, ledit dispositif de récupération de contenu haute-fréquence comprenant :
 - a) un générateur de bruit aléatoire (213) pour produire une séquence de bruit ayant un spectre donné;
 - b) une unité de mise en forme spectrale (215) pour mettre en forme le spectre de la séquence de bruit en relation avec des coefficients de filtre de prédiction linéaire reliés au signal large-bande sous-échantilloné; et
 - c) un circuit d'injection de signal (221) pour injecter ladite séquence de bruit dont le spectre a été mis en forme dans ladite version de signal synthétisé suréchantillonné pour ainsi produire ledit signal large-bande synthétisé plein spectre (223).
2. Un dispositif tel que défini dans la revendication 1, dans lequel ledit générateur de bruit aléatoire est un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc ayant un spectre plat sur toute la largeur de bande de fréquences du signal large-bande, de sorte que l'unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.
3. Un dispositif tel que défini dans la revendication 2, dans lequel ladite unité de mise en forme spectrale comporte :
 - a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
 - b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue desdits coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
 - c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subsequemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.
4. Une méthode pour récupérer un contenu haute-fréquence d'un signal large-bande préalablement sous-échantilloné et pour injecter ledit contenu haute-fréquence dans une version synthétisée suréchantillonnée dudit signal large-bande afin de produire un signal large-bande synthétisé plein spectre, ladite méthode de récupération de contenu haute-fréquence comprenant :
 - a) générer de manière aléatoire une séquence de bruit ayant un spectre donné;
 - b) mettre en forme le spectre de ladite séquence de bruit en relation avec des coefficients de filtre de prédiction linéaire reliés audit signal large-bande sous-échantilloné; et
 - c) injecter ladite séquence de bruit dont le spectre a été mis en forme dans ladite version de signal synthétisé suréchantillonné pour ainsi produire ledit signal large-bande synthétisé plein spectre.

5. Une méthode telle que définie dans la revendication 4, dans laquelle générer ladite séquence de bruit comprend générer de manière aléatoire une séquence de bruit blanc de sorte que ladite mise en forme spectrale de la séquence de bruit produit une séquence de bruit blanc dont le spectre a été mis en forme.

5 6. Une méthode telle que définie dans la revendication 5, dans laquelle ladite mise en forme spectrale de la séquence de bruit comporte :

- a) produire une séquence de bruit blanc mise à l'échelle en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain;
- 10 b) filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue desdits coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
- 15 c) filtrer à l'aide d'un filtre passe-bande ladite séquence de bruit blanc mise à l'échelle et filtrée pour produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.

7. Un décodeur pour produire un signal large-bande synthétisé, comprenant :

- 20 a) un dispositif de fragmentation de signal pour recevoir une version codée d'un signal large-bande préalablement sous-échantillonné durant le codage et extraire de ladite version de signal large-bande codée au moins des paramètres de répertoire de hauteur tonale, des paramètres de répertoire d'innovation, et des coefficients de filtre de prédiction linéaire;
- 25 b) un répertoire de hauteur tonale pour, en réponse auxdits paramètres de répertoire de hauteur tonale, produire un vecteur de code de hauteur tonale;
- c) un répertoire d'innovation pour, en réponse auxdits paramètres de répertoire d'innovation, produire un vecteur de code d'innovation;
- 30 d) un circuit de combinaison pour combiner ledit vecteur de code de hauteur tonale et ledit vecteur de code d'innovation pour ainsi produire un signal d'excitation;
- e) un dispositif de synthèse de signal incluant un filtre de prédiction linéaire pour filtrer ledit signal d'excitation en relation avec lesdits coefficients de filtre de prédiction linéaire pour ainsi produire un signal large-bande synthétisé, et un suréchantilleur pour, en réponse audit signal large-bande synthétisé, produire un version suréchantillonnée du signal large-bande synthétisé; et
- 35 f) un dispositif de récupération de contenu haute-fréquence tel que défini dans la revendication 1 pour récupérer un contenu haute-fréquence dudit signal large-bande et pour injecter ledit contenu haute-fréquence dans ladite version de signal suréchantillonnée pour produire le signal large-bande synthétisé plein spectre.

8. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 7, dans lequel ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

9. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 8, dans lequel ladite unité de mise en forme spectrale comporte :

- a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
- 50 b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue des coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
- c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.

10. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 9, comprenant

en outre :

- 5 a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
- b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et
- c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

10 dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

- 15 11. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 10, dans lequel ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

$$r_v = (E_v - E_c)/(E_v + E_c)$$

20 où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

- 25 12. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 10, dans lequel ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

$$30 \text{ Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n = 0, \dots, N-1,$$

35 où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

- 40 13. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 10, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

$$g_t = 1 - \text{tilt}$$

45 borné par $0.2 \leq g_t \leq 1.0$

où

$$50 \text{ tilt} = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

55 conditionné par $\text{tilt} \geq 0$ et $\text{tilt} \geq r_v$.

14. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 10, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

5

$$g_t = 10^{-0.6 \text{tilt}}$$

borné par $0.2 \leq g_t \leq 1.0$

où

10

15

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

20

conditionné par $\text{tilt} \geq 0$ et $\text{tilt} \geq r_v$.

15. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 9, dans lequel ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

25

16. Un décodeur pour produire un signal large-bande synthétisé, comprenant :

30

- a) un dispositif de fragmentation de signal pour recevoir une version codée d'un signal large-bande préalablement sous-échantillonné durant le codage et extraire de ladite version de signal large-bande codée au moins des paramètres de répertoire de hauteur tonale, des paramètres de répertoire d'innovation, et des coefficients de filtre de prédiction linéaire;
- b) un répertoire de hauteur tonale pour, en réponse auxdits paramètres de répertoire de hauteur tonale, produire un vecteur de code de hauteur tonale;
- c) un répertoire d'innovation pour, en réponse auxdits paramètres de répertoire d'innovation, produire un vecteur de code d'innovation;
- d) un circuit de combinaison pour combiner ledit vecteur de code de hauteur tonale et ledit vecteur de code d'innovation pour ainsi produire un signal d'excitation; et
- e) un dispositif de synthèse de signal incluant un filtre de prédiction linéaire pour filtrer ledit signal d'excitation en relation avec lesdits coefficients de filtre de prédiction linéaire pour ainsi produire un signal large-bande synthétisé, et un suréchantillonneur pour, en réponse audit signal large-bande synthétisé, produire un version suréchantillonnée du signal large-bande synthétisé;

40

le décodeur comprenant un dispositif de récupération de contenu haute-fréquence tel que défini dans la revendication 1 pour récupérer un contenu haute-fréquence dudit signal large-bande et pour injecter ledit contenu haute-fréquence dans ladite version de signal suréchantillonnée pour produire le signal large-bande synthétisé plein spectre.

45

17. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 16, dans lequel ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

50

18. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 17, dans lequel ladite unité de mise en forme spectrale comporte :

55

- a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
- b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue desdits coefficients de filtre de prédiction linéaire pour produire une sé-

quence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et

5 c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subseqüemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.

10 19. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 18, comprenant en outre :

- 15 a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et
c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

20 dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

25 20. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 19, dans lequel ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

$$r_v = (E_v - E_c)/(E_v + E_c)$$

30 où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

35 21. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 19, dans lequel ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

$$40 \text{ Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , n = 0, \dots, N-1,$$

45 où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

50 22. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 19, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

$$g_t = 1 - \text{tilt}$$

55 borné par $0.2 \leq g_t \leq 1.0$

où

5

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10 conditionné par $\text{tilt} \geq 0$ et $\text{tilt} \geq r_v$.

23. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 19, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

15

$$g_t = 10^{-0.6\text{tilt}}$$

20 borné par $0.2 \leq g_t \leq 1.0$
où

25

$$\text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

30 conditionné par $\text{tilt} \geq 0$ et $\text{tilt} \geq r_v$.

24. Un décodeur pour produire un signal large-bande synthétisé tel que défini dans la revendication 18, dans lequel ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

35

25. Un système de communication cellulaire pour desservir une grande surface géographique divisée en une pluralité de cellules, comprenant :

- a) des unités de transmission/réception mobiles;
- b) des stations de base cellulaires respectivement situées dans lesdites cellules;
- c) un terminal de contrôle pour contrôler la communication entre les stations de base cellulaires;
- 40 d) un sous-système de communication sans fil bidirectionnel entre chaque unité mobile située dans une cellule et la station de base cellulaire de ladite cellule, ledit sous-système de communication sans fil bidirectionnel comprenant, dans l'unité mobile et aussi dans la station de base cellulaire :
 - i) un transmetteur incluant un codeur pour coder un signal large-bande et un circuit de transmission pour transmettre le signal large-bande codé; et
 - ii) un récepteur incluant un circuit de réception pour recevoir un signal large-bande codé transmis et un décodeur tel que défini dans la revendication 7 pour décoder le signal large-bande codé reçu.

45

26. Un système de communication cellulaire tel que défini dans la revendication 25, dans lequel ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

50

27. Un système de communication cellulaire tel que défini dans la revendication 26, dans lequel ladite unité de mise en forme spectrale comporte :

- a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;

EP 1 125 284 B1

5 b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue des coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.

- 10 **28.** Un système de communication cellulaire tel que défini dans la revendication 27, comprenant en outre :
- 15 a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et
c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

20 dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

- 29.** Un système de communication cellulaire tel que défini dans la revendication 28, dans lequel ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

25
$$r_v = (E_v - E_c) / (E_v + E_c)$$

30 où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

- 30.** Un système de communication cellulaire tel que défini dans la revendication 28, dans lequel ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

35

40
$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , n = 0, \dots, N-1,$$

45 où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

- 31.** Un système de communication cellulaire tel que défini dans la revendication 28, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

50

$$g_t = 1 - \text{tilt}$$

borné par $0.2 \leq g_t \leq 1.0$

où

55

5

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

10

- 32.** Un système de communication cellulaire tel que défini dans la revendication 28, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

15

$$g_t = 10^{-0.6tilt}$$

borné par $0.2 \leq g_t \leq 1.0$

où

20

25

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

30

- 33.** Un système de communication cellulaire tel que défini dans la revendication 27, dans lequel ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

35

- 34.** Une unité de transmission/réception mobile cellulaire comprenant :

- a) un transmetteur incluant un codeur pour coder un signal large-bande et un circuit de transmission pour transmettre le signal large-bande codé; et
- b) un récepteur incluant un circuit de réception pour recevoir un signal large-bande codé transmis et un décodeur tel que défini dans la revendication 7 pour décoder le signal large-bande codé reçu.

40

- 35.** Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 34, dans laquelle ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

45

- 36.** Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 35, dans laquelle ladite unité de mise en forme spectrale comporte :

50

- a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
- b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue des coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
- c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de

bruit blanc ayant subi une mise en forme spectrale.

37. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 36, comprenant en outre :

- 5
a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et
10 c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

- 15
38. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 37, dans laquelle ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

20
$$r_v = (E_v - E_c) / (E_v + E_c)$$

où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

- 25
39. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 37, dans laquelle ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

30
$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , n = 0, \dots, N-1,$$

où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

- 40
40. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 37, dans laquelle ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

45
$$g_t = 1 - \text{tilt}$$

borné par $0.2 \leq g_t \leq 1.0$

où

50

55

5

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

- 15 41. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 37, dans laquelle ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

$$g_t = 10^{-0.6tilt}$$

20

borné par $0.2 \leq g_t \leq 1.0$

où

25

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

30

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

35

42. Une unité de transmission/réception mobile cellulaire telle que définie dans la revendication 36, dans laquelle ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

35

43. Un élément de réseau cellulaire comprenant :

40

- a) un transmetteur incluant un codeur pour coder un signal large-bande et un circuit de transmission pour transmettre le signal large-bande codé; et
- b) un récepteur incluant un circuit de réception pour recevoir un signal large-bande codé transmis et un décodeur tel que défini dans la revendication 7 pour décoder le signal large-bande codé reçu.

45

44. Un élément de réseau cellulaire tel que défini dans la revendication 43, dans lequel ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

50

45. Un élément de réseau cellulaire tel que défini dans la revendication 44, dans lequel ladite unité de mise en forme spectrale comporte :

55

- a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
- b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue des coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
- c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de

bruit blanc ayant subi une mise en forme spectrale.

46. Un élément de réseau cellulaire tel que défini dans la revendication 45, comprenant en outre :

- 5 a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
- b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et
- 10 c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

15 47. Un élément de réseau cellulaire tel que défini dans la revendication 46, dans lequel ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

$$r_v = (E_v - E_c) / (E_v + E_c)$$

20 où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

25 48. Un élément de réseau cellulaire tel que défini dans la revendication 46, dans lequel ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

$$30 \quad \text{Energy scaling factor} = \frac{\sqrt{\sum_{n=0}^{N-1} u'^2(n)}}{\sqrt{\sum_{n=0}^{N-1} w'^2(n)}}, \quad n = 0, \dots, N-1,$$

35 où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

40 49. Un élément de réseau cellulaire tel que défini dans la revendication 46, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

$$g_t = 1 - tilt$$

45 borné par $0.2 \leq g_t \leq 1.0$

où

$$50 \quad tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

55 conditionné par $tilt \geq 0$, et $tilt \geq r_v$

50 50. Un élément de réseau cellulaire tel que défini dans la revendication 46, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

$$g_t = 10^{-0.6 \text{tilt}}$$

borné par $0.2 \leq g_t \leq 1.0$

5 où

$$10 \quad \text{tilt} = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

15 conditionné par $\text{tilt} \geq 0$ et $\text{tilt} \geq r_v$.

51. Un élément de réseau cellulaire tel que défini dans la revendication 45, dans lequel ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

20 52. Un système de communication cellulaire pour desservir une grande surface géographique divisée en une pluralité de cellules, comprenant : des unités de transmission/réception mobiles; des stations de base cellulaires, respectivement situées dans lesdites cellules; et un terminal de contrôle pour contrôler la communication entre les stations de base cellulaires;
25 un sous-système de communication sans fil bidirectionnel entre chaque unité mobile située dans une cellule et la station de base cellulaire de ladite cellule, ledit sous-système de communication sans fil bidirectionnel comprenant, dans l'unité mobile et aussi dans la station de base cellulaire :

30 a) un transmetteur incluant un codeur pour coder un signal large-bande et un circuit de transmission pour transmettre le signal large-bande codé; et
b) un récepteur incluant un circuit de réception pour recevoir un signal large-bande codé transmis et un décodeur tel que défini dans la revendication 7 pour décoder le signal large-bande codé reçu.

35 53. Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 52, dans lequel ledit générateur de bruit aléatoire comporte un générateur de bruit blanc aléatoire pour produire une séquence de bruit blanc de sorte que ladite unité de mise en forme spectrale produit une séquence de bruit blanc dont le spectre a été mis en forme.

40 54. Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 53, dans lequel ladite unité de mise en forme spectrale comporte :

45 a) un module d'ajustement de gain pour, en réponse à ladite séquence de bruit blanc et un jeu de paramètres d'ajustement de gain, produire une séquence de bruit blanc mise à l'échelle;
b) un conformateur spectral pour filtrer ladite séquence de bruit blanc mise à l'échelle en relation avec une version à largeur de bande étendue des coefficients de filtre de prédiction linéaire pour produire une séquence de bruit blanc mise à l'échelle et filtrée comprenant une largeur de bande de fréquences généralement plus élevée qu'une largeur de bande de fréquences de ladite version de signal synthétisée suréchantillonnée; et
c) un filtre passe-bande pour, en réponse à ladite séquence de bruit blanc mise à l'échelle et filtrée, produire une séquence de bruit blanc mise à l'échelle ayant subi un filtrage passe-bande et destinée à être subséquemment injectée dans ladite version de signal synthétisée suréchantillonnée comme ladite séquence de bruit blanc ayant subi une mise en forme spectrale.

50 55. Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 54, comprenant en outre :

55 a) un générateur de facteur de voisement pour, en réponse auxdits vecteurs de codes de hauteur tonale et d'innovation, calculer un facteur de voisement pour transmission audit module d'ajustement de gain;
b) un module de calcul d'énergie pour, en réponse audit signal d'excitation, calculer une énergie d'excitation pour transmission audit module d'ajustement de gain; et

EP 1 125 284 B1

c) un calculateur d'inclinaison spectrale pour, en réponse audit signal synthétisé, calculer un facteur de mise à l'échelle d'inclinaison pour transmission audit module d'ajustement de gain;

dans lequel ledit jeu de paramètres d'ajustement de gain comprend ledit facteur de voisement, ladite énergie d'excitation, et ledit facteur de mise à l'échelle d'inclinaison.

- 56.** Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 55, dans lequel ledit générateur de facteur de voisement comporte un moyen pour calculer ledit facteur de voisement r_v utilisant la relation :

10

$$r_v = (E_v - E_c) / (E_v + E_c)$$

où E_v est l'énergie d'une version mise à l'échelle par un gain du vecteur de code de hauteur tonale et E_c est l'énergie d'une version mise à l'échelle par un gain du vecteur de code d'innovation.

- 57.** Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 55, dans lequel ladite unité d'ajustement de gain comprend un moyen pour calculer un facteur de mise à l'échelle d'énergie utilisant la relation :

20

25

$$\text{Energy scaling factor} = \sqrt{\frac{\sum_{n=0}^{N-1} u'^2(n)}{\sum_{n=0}^{N-1} w'^2(n)}} , n = 0, \dots, N'-1,$$

où w' est ladite séquence de bruit blanc et u' est un signal d'excitation rehaussé dérivé dudit signal d'excitation.

30

- 58.** Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 55, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

35

$$g_t = 1 - tilt$$

borné par $0.2 \leq g_t \leq 1.0$

où

40

45

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

50

- 59.** Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 56, dans lequel ledit calculateur d'inclinaison spectrale comprend un moyen pour calculer ledit facteur de mise à l'échelle d'inclinaison g_t utilisant la relation :

55

$$g_t = 10^{-0.6tilt}$$

bomé par $0.2 \leq g_t \leq 1.0$

où

5

$$tilt = \frac{\sum_{n=1}^{N-1} s_h(n)s_h(n-1)}{\sum_{n=0}^{N-1} s_h^2(n)}$$

10

conditionné par $tilt \geq 0$ et $tilt \geq r_v$.

15

- 60.** Un sous-système de communication sans fil bidirectionnel tel que défini dans la revendication 54, dans lequel ledit filtre passe-bande comporte une largeur de bande de fréquences située entre 5.6 kHz et 7.2 kHz.

20

25

30

35

40

45

50

55







